



MANNINGTON COMMERCIAL PRODUCT CARE GUIDELINES

Wall Base & Chair Rail Molding



INTRODUCTION

Mannington Commercial wall base of any type and chair rail molding normally require little maintenance. Due to their refined and smooth surface, and their natural luster, minimal attention is required.



WALL BASE REGULAR CLEANING

For routine cleaning, wipe base with a microfiber rag. This is generally sufficient to restore the wall base finish and appearance. A spray-on neutral cleaner or glass cleaner will normally do the job. Be careful not to overspray cleaner onto painted walls or wall covering.



WALL BASE SCUFF REMOVAL

Shoe sole marks, marks from cleaning equipment and other rolling stock can be unsightly and require removal. Most of these marks can be removed with a microfiber rag and a neutral cleaner. Abrasive cleaners like Comet are not recommended.



WALL BASE FINISH OR WAX REMOVAL

Finishing or waxing of Mannington Commercial Wall Base is not recommended. It is not required and can be unsightly and objectionable. If any finish or wax should accidentally be splashed onto the wall base surface as finish is being applied to the adjacent flooring, it can be removed using a gentle hand application of a neutral pH wax remover. Care should be taken not to over-clean any spots on the wall base, to prevent surface color variation that may become more noticeable than any discoloration occurring from the waxed area.



CHAIR RAIL MOLDING MAINTENANCE

1. Do not perform any maintenance on the product for 24 hours after installation is completed.
2. Thoroughly wipe the entire surface area to remove all dust, dirt and grit.
3. Prepare a cleaning solution by mixing 1 oz. to 4 oz. of a neutral detergent (pH of 7-8) per gallon of warm water. The dilution selected depends on light to heavy soil conditions.
4. Scrub the chair rail molding surface with the solution using a clean microfiber rag.

