

## Liminal Space Collection

Style	Inclination (Modular)	Locus (Modular)
<b>Construction</b>	Textured Patterned Loop	Textured Patterned Loop
<b>Face Fiber</b>	Type 6,6 Nylon	Type 6,6 Nylon
<b>Dye Method</b>	Solution	Solution
<b>Gauge</b>	1/12 (4724 per 10 cm)	1/12 (4724 per 10 cm)
<b>Stitches Per Inch</b>	11 (43.31 per 10cm)	12 (4724 per 10 cm)
<b>Density</b>	5,702 (211.87 kg/m3)	5,298 (196.86 kg/m3)
<b>Pile Thickness</b>	.113" (2.87mm)	.106" ( 2.69 mm)
<b>Weight</b>	18 oz/yd2 610 g/m2)	16 oz/yd2 (542 g/m2)
<b>Backing Type</b>	Infinity® 2 Modular-rEvolve® II Modular	Infinity® 2 Modular-rEvolve® II Modular
<b>Sizes</b>	12 x 36 (30.48 X 91.44 cm)	12 x 36 (30.48 X 91.44 cm)
<b>Colors</b>	9	9
<b>Packaging</b>	5.33 yd2 / 16 Tiles	5.33 yd2 / 16 Tiles
<b>Adhesive</b>	Infinity 2 Adhesive XpressStep Spray FreLock Tabs - Infinity 2 Modular only	Infinity 2 Adhesive XpressStep Spray FreLock Tabs - Infinity 2 Modular only
<b>Installation Method</b>	Vertical Ashlar	Vertical Ashlar
<b>Testing</b>		
<b>Dimensional Stability (Aachen Test)</b>	Passes	Passes
<b>Electrostatic Propensity (AATCC 134)</b>	Less than 3.0 kV	Less than 3.0 kV
<b>Radiant Panel (ASTM E648)</b>	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
<b>Smoke Density (ASTM E662)</b>	≤ 450-Passes	≤ 450-Passes
<b>Methenamine Pill Test (ASTM D2859)</b>	Passes	Passes
<b>Hexapod (ASTM D5252) TARR Rating</b>	3.0	3.0
<b>Environmental Data</b>		
<b>NSF/ANSI 140 Certification</b>	Infinity 2 Modular - Gold / rEvolve® II Modular -Gold	
<b>Recycled Content</b>	Contains recycled content	
<b>Indoor Air Quality</b>	CRI Green Label Plus Certified	
<b>Product Declarations</b>	Third Party Verified EPD, HPD	
<b>Carbon Offset</b>	105% Cradle to Gate (A1 - A3), visit website for more information	
<b>LEED</b>	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Green Label Plus certificate	
<b>mindful MATERIALS</b>	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
<b>Manufacturing</b>	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Verified Silver	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Limited 15-Year XGUARD® Stain Resistant Limited 15-Year ColorSafe® Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

## Liminal Space Collection

Style	Parallax (Broadloom)	Parallax (Modular)
<b>Construction</b>	Tip- Sheared Patterned Loop	Tip- Sheared Patterned Loop
<b>Face Fiber</b>	Type 6,6 Nylon	Type 6,6 Nylon
<b>Dye Method</b>	Solution	Solution
<b>Gauge</b>	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
<b>Stitches Per Inch</b>	10 (39.37 per 10 cm)	10 (39.37 per 10 cm)
<b>Density</b>	7,047 (261.85 kg/m <sup>3</sup> )	7,047 (261.85 kg/m <sup>3</sup> )
<b>Pile Thickness</b>	.118" (3.00 mm)	.118" (3.00 mm)
<b>Weight</b>	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )
<b>Backing Type</b>	UltraBac® RE, Integra® HP	Infinity® 2 Modular-rEvolve® II Modular
<b>Sizes</b>	12'6" width (3.81m)	12 x 36 (30.48 X 91.44 cm)
<b>Pattern Repeat</b>	72" Wx 72" L (182.88 x 182.88cm)	N/a
<b>Colors</b>	9	9
<b>Packaging</b>	N/a	5.33 yd <sup>2</sup> / 16 Tiles
<b>Adhesive</b>	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs - Infinity 2 Modular only
<b>Installation Method</b>	N/a	Vertical Ashlar
<b>Testing</b>		
<b>Dimensional Stability (Aachen Test)</b>	Passes	Passes
<b>Electrostatic Propensity (AATCC 134)</b>	Less than 3.0 kV	Less than 3.0 kV
<b>Radiant Panel (ASTM E648)</b>	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)
<b>Smoke Density (ASTM E662)</b>	≤ 450-Passes	≤ 450-Passes
<b>Methenamine Pill Test (ASTM D2859)</b>	Passes	Passes
<b>Hexapod (ASTM D5252) TARR Rating</b>	3.0	3.0
<b>Environmental Data</b>		
<b>NSF/ANSI 140 Certification</b>	<b>Broadloom:</b> UltraBac® RE - Gold, Integra® HP - Gold <b>Modular:</b> Infinity 2 Modular - Gold / rEvolve II Modular - Gold	
<b>Recycled Content</b>	Contains recycled content	
<b>Indoor Air Quality</b>	CRI Green Label Plus Certified	
<b>Product Declarations</b>	Third Party Verified EPD, HPD	
<b>Carbon Offset</b>	105% Cradle to Gate (A1 - A3), visit website for more information	
<b>LEED</b>	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Green Label Plus certificate	
<b>mindful MATERIALS</b>	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
<b>Manufacturing</b>	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Verified Silver	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Limited 15-Year XGUARD® Stain Resistant Limited 15-Year ColorSafe® Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

## Liminal Space Collection

Style	Reverie (Broadloom)	Reverie (Modular)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10 cm)	10 (39.37 per 10 cm)
Density	7,107 (264.08 kg/m <sup>3</sup> )	7,107 (264.08 kg/m <sup>3</sup> )
Pile Thickness	.116" (2.95 mm)	.116" (2.95 mm)
Weight	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular-rEvolve® II Modular
Sizes	12'6" width (3.81m)	12 x 36 (30.48 X 91.44 cm)
Pattern Repeat	72" W x 72" L(182.88 x 182.88cm)	N/a
Colors	9	9
Packaging	N/a	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs - Infinity 2 Modular only
Installation Method	N/a	Vertical Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Radiant Panel (ASTM E648)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR Rating	3.0	3.0
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	<b>Broadloom:</b> UltraBac® RE - Gold, Integra® HP - Gold <b>Modular:</b> Infinity 2 Modular - Gold / rEvolve II Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Green Label Plus certificate	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Verified Silver	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Limited 15-Year XGUARD® Stain Resistant Limited 15-Year ColorSafe® Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

## Liminal Space Collection

Style	Threshold (Broadloom)	Threshold (Modular)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10 cm)	10 (39.37 per 10 cm)
Density	7,333 (272.48 kg/m <sup>3</sup> )	7,333 (272.48 kg/m <sup>3</sup> )
Pile Thickness	.108" (2.74 mm)	.108" (2.74 mm)
Weight	22 oz/yd <sup>2</sup> (746 g/m <sup>2</sup> )	22 oz/yd <sup>2</sup> (746 g/m <sup>2</sup> )
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular-rEvolve® II Modular
Sizes	12' 6" width (3.81m)	12 x 36 (30.48 X 91.44 cm)
Pattern Repeat	72" W x 72" L (182.88 x 182.88 cm)	N/a
Colors	9	9
Packaging	N/a	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs - Infinity 2 Modular only
Installation Method	N/a	Vertical Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Radiant Panel (ASTM E648)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR Rating	3.0	3.0
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	<b>Broadloom:</b> UltraBac® RE - Gold, Integra® HP - Gold <b>Modular:</b> Infinity 2 Modular - Gold / rEvolve II Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Green Label Plus certificate	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Verified Silver	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Limited 15-Year XGUARD® Stain Resistant Limited 15-Year ColorSafe® Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262