



Proxy Collection

**Mannington**  
COMMERCIAL



**Cover: Wood** - Andara Oak PRX204  
**Above: Wood** - Spice Oak PRX207, **Stone** - Antler Velvet PRX301



Wood - Lichen Oak PRX205, Grounding Oak PRX202



Wood - Mink Oak PRX203, Elevate Rug Urban Grid - Pewter Graphite 450

# Crafted for Stewardship

Through our commitment to environmental and social responsibility, we are making strides toward delivering flooring solutions that have a positive impact. Mannington Commercial's Proxy is uniquely crafted to perform with Quantum Guard Elite® and sustain with leading product certifications.

## Commitment to Environmental Sustainability

- 100% Free of PVC, Ortho-phthalates, PFAS/PFOS, Halogens, Plasticizers and Chlorine
- 105% Carbon Offset Cradle to Gate
- Third party Verified EPD and HPD
- Declare Red List Free

## Big Picture Benefits

- Quantum Guard Elite® Technology for superior scratch and dent resistance
- Engineered for best-in-class dimensional stability
- 20 mil Wear Layer
- Easy no-polish maintenance significantly reduces overall life cycle cost and total cost of ownership

Crafted with Purpose.



# Defeat Damp Spaces

**Your job just got easier.** With our comprehensive moisture solutions for LVT, you can defeat the most extreme high moisture conditions.

**Best Solutions for:**

## Any Slab Condition

**NO Moisture Testing Required – NO RH limit, NO Testing\***

### Adhesive

---

MoistureLoc

**\* Conditions**

No hydrostatic pressure | No standing water or visible water stains | Slab is at least 45 days old

**Best Solutions for:**

## Slabs with Intact Vapor Barrier (Class B or better)

**Quick pH Testing Required\*\***

### Adhesive

---

**pH**

V-88

12

MoistureLoc

None

QuickStix® with Moisture Resistant Primer\*\*

12

**\*\* Conditions**

Intact Class B or better vapor barrier | No hydrostatic pressure | No standing water or visible water stains | Slab is at least 45 days old

**Best Solutions for:**

## Unknown Slab Conditions

**Moisture Testing Required**

### Adhesive

---

**RH%**

**MVER**

**pH**

V-88

95

10

12

MoistureLoc

None

None

None

XpressStep LVT

98

10

12

QuickStix® with Premium Universal Primer (with IVB)

99

18

12

QuickStix® with Premium Universal Primer (No IVB)

95

10

12

V-95

85

5

9

IVB = Intact Vapor Barrier

**Proxy Collection | Stone & Wood**

Style	Stone	Wood
Construction	Polymeric Composite Non-Vinyl Flooring Non-ortho Phthalate	Polymeric Composite Non-Vinyl Flooring Non-ortho Phthalate
Classification	Commercial	Commercial
Total Thickness	0.098" (2.5 mm)	0.098" (2.5 mm)
Wear Layer Thickness	20 mil (0.51 mm)	20 mil (0.51 mm)
Wear Layer	Quantum Guard Elite®	Quantum Guard Elite®
Edge Treatment	Square Edge	Square Edge
Sizes	18" x 18" (457 x 457 mm)	725" x 48" (184 x 1219 mm)
Colors	2	8
Packaging	18" x 18" - 12 pcs, 21.01 ft <sup>2</sup> (2.51 m <sup>2</sup> ), 24.96 lbs (11.3 kg)	725" x 48" - 9 pcs, 21.74 ft <sup>2</sup> (2.02 m <sup>2</sup> ), 20.30 lbs (9.2 kg)
Adhesive	<p><b>Porous &amp; Non-porous Substrates:</b>  <b>V-88 Full Spread</b>  <b>MoistureLoc Full Spread, One Component</b>  <b>V-95 Full Spread, 2-part Epoxy</b>  <b>XpressStep for LVT &amp; Sheet Vinyl Full Coverage Spray</b></p> <p><b>Note:</b> Must use V-95, MoistureLoc or XpressStep adhesive under hospital beds and heavy rolling load areas. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95 or MoistureLoc should be used.</p>	
Installation Method	<p>All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.</p>	
<b>Testing</b>		
HUD/FHA	Passes	
Flexibility (ASTM F137)	Passes - 1.5" Mandrel - No Crack/Break	
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft	
Squareness (ASTM F540)	Passes - Max 0.010"	
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"	
Residual Indentation (ASTM F1914)	Passes - ≤ 0.007"	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Slip Resistance - Dry (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Resistance to Light (ASTM F1515)	Passes	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
<b>Environmental Data</b>		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), see website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS Manufacturing	Visit mindfulmaterials.com for current transparency information China	
<b>Warranty</b>	Limited 15-Year Commercial Warranty Limited 15-Year Quantum Guard Elite® Wear Warranty	