

Proxy Collection | Stone & Wood

Style	Stone	Wood
Construction	Polymeric Composite Non-Vinyl Flooring Non-ortho Phthalate	Polymeric Composite Non-Vinyl Flooring Non-ortho Phthalate
Classification	Commercial	Commercial
Total Thickness	0.098" (2.5 mm)	0.098" (2.5 mm)
Wear Layer Thickness	20 mil (0.51 mm)	20 mil (0.51 mm)
Wear Layer	Quantum Guard Elite®	Quantum Guard Elite®
Edge Treatment	Square Edge	Square Edge
Sizes	18" x 18" (457 x 457 mm)	72.5" x 48" (184 x 1219 mm)
Colors	2	8
Packaging	18" x 18" - 12 pcs, 27.01 ft ² (2.51 m ²), 24.96 lbs (11.3 kg)	72.5" x 48" - 9 pcs, 21.74 ft ² (2.02 m ²), 20.30 lbs (9.2 kg)
Adhesive	<p>Porous & Non-porous Substrates: V-88 Full Spread MoistureLoc Full Spread, One Component V-95 Full Spread, 2-part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray Note: Must use V-95, MoistureLoc or XpressStep adhesive under hospital beds and heavy rolling load areas. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95 or MoistureLoc should be used.</p> <p>Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.</p> <p>All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.</p>	
QuickStix®		
Installation Method		
Testing		
HUD/FHA	Passes	
Flexibility (ASTM F137)	Passes - 1.5" Mandrel - No Crack/Break	
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/in ft	
Squareness (ASTM F540)	Passes - Max 0.010"	
Static Load (ASTM F970 mod.)	Passes - 2,000 PSI; Residual Indent ≤ 0.005"	
Residual Indentation (ASTM F1914)	Passes - ≤ 0.007"	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - ≤ 450	
Slip Resistance - Dry (ASTM C1028)	Passes - ≥ 0.5 Leather; 0.6 Rubber	
Resistance to Light (ASTM F1515)	Passes	
Chemical Resistance (ASTM F925)	Passes	
Resistance to Heat (ASTM F1514)	Passes	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), see website for more information	
LEED	<p>May contribute to LEED credits:</p> <ul style="list-style-type: none"> Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials 	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information	
Manufacturing	China	
Warranty	<p>Limited 15-Year Commercial Warranty Limited 15-Year Quantum Guard Elite® Wear Warranty</p>	