

Safety Data Sheet

According To Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules And Regulations

Revision Date: 3/18/2026

Date of Issue: 3/18/2026

Version: 1.0

SECTION 1: IDENTIFICATION**1.1. Product Identifier****Product Form:** Mixture**Product Name:** Mannington Performance Urethane**1.2. Intended Use of the Product****Use of the Substance/Mixture:** Adhesives and/or sealants**1.3. Name, Address, and Telephone of the Responsible Party****Mannington Mills, Inc.****75 Mannington Mills Road****Salem, New Jersey 08079 U.S.A.****General Information: (800) 241-2262****1.4. Emergency Telephone Numbers****Product/Medical Emergency Phone Number (24 Hours): (866) 359-5602****Transport Emergency:****Within the U.S. - CHEMTREC: (800) 424-9300****Outside the U.S. – CHEMTREC: +1-703-527-3887****SECTION 2: HAZARDS IDENTIFICATION****2.1. Classification of the Substance or Mixture****GHS-US Classification**

Eye irritation, Category 2A

H319

Causes serious eye irritation.

Respiratory Sensitization, Category 1

H334

May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Sensitization, Category 1

H317

May cause an allergic skin reaction.

Carcinogenicity, Category 2

H351

Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

Full text of hazard classes and H-statements : see section 16

2.2. Label Elements**GHS-US Labeling****Hazard Pictograms (GHS-US)**

:



GHS08

Signal Word (GHS-US)

: Danger

Hazard Statements (GHS-US)

: H317 May cause an allergic skin reaction.

H319 Causes serious eye irritation.

H334 May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H351 Suspected of causing cancer if inhaled, in contact with skin and if swallowed.

Precautionary Statements (GHS-US)

: P201 Obtain special instructions before use.

P202 Do not handle until all safety precautions have been read and understood.

P261 Avoid breathing mist/vapours/spray.

P264 Wash skin thoroughly after handling.

P280 Wear protective gloves/clothing and eye/face protection.

P284 [In case of inadequate ventilation] wear respiratory protection. P302+P352
IF ON SKIN: Wash with plenty of water.

P304+P340 IF INHALED: Remove person to fresh air and keep comfortable for breathing.

P305+P351+P338 IF IN EYES: Rinse cautiously with water for several minutes.

Remove contact lenses, if present and easy to do. Continue rinsing.

P308+P313 IF exposed or concerned: Call a POISON CENTER/ doctor/...

P333+P313 If skin irritation or rash occurs: Get medical advice/attention.

P337+P313 UN5\$P337+P313

P342+P311 If experiencing respiratory symptoms: Call a doctor. P362+P364 Take off contaminated clothing and wash it before reuse.

P501 Dispose of contents/container in accordance with applicable regulations.

Mannington Performance Urethane

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

2.3. Other Hazards

Exposure may aggravate pre-existing eye, skin, or respiratory conditions.

2.4. Unknown Acute Toxicity (GHS-US)

None

2.5. Hazards not otherwise classified identified during the classification process

None

This product contains crystalline silica (quartz sand). IARC has classified crystalline silica as a Group 1 carcinogen. Both IARC and NTP consider silica as a known human carcinogen. Evidence is based on the chronic and long-term exposure workers have had to respirable sized crystalline silica dust particles. Because this product is in liquid or paste form, it does not pose a dust hazard; therefore, this classification is not relevant. (Note: sanding of the hardened product may create a silica dust hazard)

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1. Substance

Not applicable

3.2. Mixture

Hazardous components within the meaning of 29 CFR 1910.1200 and related classification:

List of components:

Qty	Name	Ident. Numb.	Classification
≥1 - <5 %	calcium oxide; quicklime	CAS:1305-78-8 EC:215-138-9	STOT SE 3, H335; Skin Irrit. 2, H315; Eye Dam. 1, H318
≥0.1 - <1 %	4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluene	CAS:4083-64-1 EC:223-810-8 EU CLP Index:615-012-00-7	Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334
≥0.1 - <1 %	4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	CAS:101-68-8 EC:202-966-0 EU CLP Index:615-005-00-9	Acute Tox. 4, H332; Eye Irrit. 2A, H319; STOT SE 3, H335; Skin Irrit. 2, H315; Resp. Sens. 1, H334; Skin Sens. 1, H317; STOT RE 2, H373; Carc. 2, H351
≥0.1 - <1 %	silica sand; quartz	CAS:14808-60-7 EC:238-878-4	STOT RE 1, H372; Carc. 1A, H350

The specific chemical identity and/or exact percentage of composition have been withheld as a trade secret [29 CFR 1910.1200]

Full text of H-phrases: see section 16

SECTION 4: FIRST AID MEASURES

4.1. Description of First-aid Measures

In case of skin contact:

Immediately take off all contaminated clothing.

OBTAIN IMMEDIATE MEDICAL ATTENTION.

Obtain medical attention if skin related symptoms persist.

Remove contaminated clothing immediately and dispose of safely.

After contact with skin, wash immediately with soap and plenty of water.

In case of eyes contact:

After contact with the eyes, rinse with water with the eyelids open for a sufficient length of time, then consult an ophthalmologist immediately.

Protect uninjured eye.

In case of Ingestion:

Do not induce vomiting, get medical attention showing the SDS and the hazard label.

In case of Inhalation:

Remove exposed person(s) to fresh air and keep warm and at rest.

4.2. Most Important Symptoms and Effects Both Acute and Delayed

Eye Irritation

Eye Damages

Indication of any immediate medical attention and special treatment needed

In case of accident or unwellness, seek medical advice immediately (show directions for use or safety data sheet if possible).

Treatment:

(see paragraph 4.1)

Mannington Performance Urethane

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

SECTION 5: FIRE-FIGHTING MEASURES

5.1. Extinguishing Media

Suitable Extinguishing Media: Water, Carbon Dioxide (CO₂)

Unsuitable Extinguishing Media: None known

5.2. Special Hazards Arising From the Substance or Mixture

Do not inhale explosion and combustion gases.

Burning produces heavy smoke.

Hazardous combustion products: Not available

Explosive properties: Not Relevant

Oxidizing properties: Not Relevant

5.3. Advice for Firefighters

Use suitable breathing apparatus.

Collect contaminated fire extinguishing water separately. This must not be discharged into drains.

Move undamaged containers from immediate hazard area if it can be done safely.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1. Personal Precautions, Protective Equipment and Emergency Procedures

Wear personal protection equipment.

Remove persons to safety.

Do not allow to enter into soil/subsoil.

Do not allow to enter into surface water or drains.

Limit leakages with earth or sand.

6.2. Methods and Materials for Containment and Cleaning Up

Suitable material for taking up: absorbing material, organic, sand

Retain contaminated washing water and dispose it.

6.3. Reference to Other Sections

See Section 8 for exposure controls and personal protection and Section 13 for disposal considerations.

SECTION 7: HANDLING AND STORAGE

7.1. Precautions for Safe Handling

Avoid contact with skin and eyes, inhalation of vapors and mists.

Exercise the greatest care when handling or opening the container.

Don't use empty container before they have been cleaned.

Before making transfer operations, assure that there aren't any incompatible material residuals in the containers. Contaminated clothing should be changed before entering eating areas.

Do not eat or drink while working.

See also section 8 for recommended protective equipment.

Other Information: Wash hands and other exposed areas with mild soap and water before eating, drinking or smoking and when leaving work. Obtain special instructions before use. Do not breathe dust. Do not handle until all safety precautions have been read and understood. Do not get in eyes, on skin, or on clothing. Avoid contact with skin, eyes and clothing.

Hygiene Measures: Handle in accordance with good industrial hygiene and safety procedures.

7.2. Conditions for Safe Storage, Including Any Incompatibilities

Technical Measures: Comply with applicable regulations.

Storage Conditions: Keep away from food, drink, and feed. Keep container closed when not in use. Store in a dry, cool place. Keep/Store away from direct sunlight, extremely high or low temperatures and incompatible materials. Adequately ventilated premises.

Incompatible Products: None in particular

7.3. Specific End Use(s)

Adhesives and/or sealants

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1. Control Parameters

For substances listed in section 3 that are not listed here, there are no established exposure limits from the manufacturer, supplier, importer, or the appropriate advisory agency including: ACGIH (TLV), AIHA (WEEL), NIOSH (REL), or OSHA (PEL).

Mannington Performance Urethane

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

	OEL Type	Country	Occupational Exposure Limit
calcium oxide; quicklime CAS: 1305-78-8	ACGIH		Long Term: 2 mg/m3 URT irr
	MAK	GERMANY	Long Term: 1 mg/m3 OSHA
	OSHA		Long Term: 5 mg/m3
	ACGIH		Long Term: 2 mg/m3 upper respiratory tract irritation
	MAK	AUSTRIA	Long Term: 1 mg/m3; Short Term: 4 mg/m3
	MAK	SWITZERLAND	Long Term: 2 mg/m3
	EU		Long Term: 1 mg/m3; Short Term: 4 mg/m3 Respirable fraction
4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-CAS: 101-68-8	ACGIH		Long Term: 0.005 ppm Resp sens
	MAK	GERMANY	Long Term: 0.05 mg/m3
	ACGIH		Long Term: 0.05 mg/m3 respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
	OSHA		Short Term: Ceiling - 0.2 mg/m3 - 0.02 ppm
	MAK	AUSTRIA	Long Term: 0.05 mg/m3 - 0.005 ppm; Short Term: 0.1 mg/m3 - 0.01 ppm
	ACGIH		Long Term: 0.005 ppm respiratory sensitization (listed under Methylene bisphenyl isocyanate (MDI))
	OSHA		Short Term: Ceiling - 0.2 mg/m3 - 0.02 ppm
	EU		Long Term: 0.006 mg/m3; Short Term: 0.012 mg/m3 Skin; Dermal and respiratory sensitisation
silica sand; quartz CAS: 14808-60-7	ACGIH		Long Term: 0.025 mg/m3 A2 - Suspected Human Carcinogen;lung cancer;pulmonary fibrosis
	MAK	AUSTRIA	Long Term: 0.15 mg/m3
	ACGIH		Long Term: 0.025 mg/m3 (R), A2 - Pulm fibrosis, lung cancer'
	MAK	SWITZERLAND	Long Term: 0.15 mg/m3
	EU		Long Term: 0.1 mg/m3 Behaviour Binding

Mannington Performance Urethane


8.2. Exposure Controls

Appropriate Engineering Controls

: Emergency eye wash fountains and safety showers should be available in the immediate vicinity of any potential exposure. Ensure adequate ventilation, especially in confined areas. Gas detectors should be used when toxic gases may be released. Ensure all national/local regulations are observed.

Personal Protective Equipment

: Gloves. Protective clothing. Protective goggles. Insufficient ventilation: wear respiratory protection.



Materials for Protective Clothing

: Chemically resistant materials and fabrics.

Hand Protection

: Wear protective gloves.

Eye Protection

: Chemical safety goggles.

Skin and Body Protection

: Wear suitable protective clothing.

Respiratory Protection

: If exposure limits are exceeded or irritation is experienced, approved respiratory protection should be worn. In case of inadequate ventilation, oxygen deficient atmosphere, or where exposure levels are not known wear approved respiratory protection.

Other Information

: When using, do not eat, drink or smoke.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on Basic Physical and Chemical Properties

Physical State	: Liquid
Appearance	: Paste white
Odor	: characteristic
Odor Threshold	: No data available
pH	: No data available
Evaporation Rate	: No data available
Melting Point	: No data available
Freezing Point	: No data available
Boiling Point	: No data available
Flash Point	: 94 °C (201 °F)
Auto-ignition Temperature	: No data available
Decomposition Temperature	: No data available
Flammability (solid, gas)	: No data available
Vapor Pressure	: No data available
Relative Vapor Density at 20°C	: No data available
Relative Density	: No data available
Specific Gravity / Density	: 1.50 g/cm ³
Solubility in water	: immiscible
Solubility in oil	: Partly soluble
Partition Coefficient: N-Octanol/Water	: No data available
Viscosity	: 100,000.00 mPA-s

Mannington Performance Urethane

Safety Data Sheet

According to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

9.2. Other Information

VOC Content : <40 g/l

SECTION 10: STABILITY AND REACTIVITY

- 10.1. **Reactivity:** Hazardous reactions will not occur under normal conditions.
10.2. **Chemical Stability:** Data not available
10.3. **Possibility of Hazardous Reactions:** None
10.4. **Conditions to Avoid:** Stable under normal conditions
10.5. **Incompatible Materials:** None in particular
10.6. **Hazardous Decomposition Products:** None

SECTION 11: TOXICOLOGICAL INFORMATION

11.1. Information on Toxicological Effects

Acute Toxicity: Not classified

Skin Corrosion/Irritation: Not classified.

Serious Eye Damage/Irritation: The product is classified: Eye irritation, Category 2A(H319)

Respiratory or Skin Sensitization: The product is classified: Respiratory Sensitization, Category 1(H334), Skin Sensitization, Category 1(H317)

Germ Cell Mutagenicity: Not classified.

Carcinogenicity: The product is classified: Carcinogenicity, Category 2(H351)

Reproductive Toxicity: Not classified

Specific Target Organ Toxicity (Single Exposure): Not classified.

Specific Target Organ Toxicity (Repeated Exposure): Not classified.

Aspiration Hazard: Not classified

Toxicological information on main components of the mixture:

calcium oxide; quicklime	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg
		LD50 Skin Rat > 2500 mg/kg
4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluen e	a) acute toxicity	LC50 Inhalation Rat > 640 ppm 1h
		LD50 Oral Rat = 2234 mg/kg
4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	a) acute toxicity	LD50 Oral Rat > 2000 mg/kg
	f) carcinogenicity	Carcinogenicity Inhalation Rat = 6 mg/m3 2Y
	g) reproductive toxicity	NOAEL Inhalation Rat = 12 mg/m3 20 d
silica sand; quartz	a) acute toxicity	LD50 Oral > 2000 mg/kg
		LD50 Skin > 2000 mg/kg

Substance(s) listed on the IARC Monographs:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- Group 3
silica sand; quartz Group 1

Substance(s) listed as OSHA Carcinogen(s):

silica sand; quartz

Substance(s) listed as NIOSH Carcinogen(s):

silica sand; quartz

Substance(s) listed on the NTP report on Carcinogens:

silica sand; quartz

Mannington Performance Urethane

SECTION 12: ECOLOGICAL INFORMATION

12.1. Toxicity

Ecology - General

: The ecotoxicological information applies to the materials bound within the product.

Component	Ident. Numb.	Ecotox Data		
calcium oxide; quicklime	CAS: 1305-78-8- EINECS: 215-138-9	a) Aquatic acute toxicity : LC50 Fish = 457 mg/L 96		
		a) Aquatic acute toxicity : EC50 Daphnia = 49.1 mg/L 48		
		b) Aquatic chronic toxicity : NOEC Daphnia = 32 mg/L - 14 d		
		a) Aquatic acute toxicity : LC50 Fish = 50.6 mg/L 96		
		a) Aquatic acute toxicity : LC50 Daphnia = 158 mg/L 96		
		a) Aquatic acute toxicity : EC50 Algae = 184.57 mg/L 72		
		b) Aquatic chronic toxicity : NOEC Algae = 48 mg/L 72		
		a) Aquatic acute toxicity : LC50 Fish Cyprinus carpio = 1070 mg/L 96h IUCLID		
		4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-	CAS: 101-68-8 - 96 EINECS: 202-966-0 - INDEX:615-005-00-9	a) Aquatic acute toxicity : LC50 Fish > 1000 mg/L
				a) Aquatic acute toxicity : EC50 Daphnia > 1000 mg/L 24
b) Aquatic chronic toxicity : NOEC Daphnia > 10 mg/L - 21 d				
a) Aquatic acute toxicity : EC50 Algae > 1640 mg/L 72				
c) Bacteria toxicity : EC50 > 100 mg/L 3				
d) Terrestrial toxicity : NOEC > 1000 mg/kg - 14 d				
e) Plant toxicity : NOEC > 1000 mg/kg - 14 d				

12.2. Other Adverse Effects

Other Information

: Avoid release to the environment.

SECTION 13: DISPOSAL CONSIDERATIONS

13.1. Waste Treatment Methods

The generation of waste should be avoided or minimized wherever possible. Recover if possible.

Methods of disposal:

Disposal of this product, solutions, packaging and any by-products should at all times comply with the requirements of environmental protection and waste disposal legislation and any regional local authority requirements.

Dispose of surplus and nonrecyclable products via a licensed waste disposal contractor.

Do not dispose of waste into sewers.

Disposal considerations:

Do not allow to enter drains or watercourses.

Dispose of product according to all federal, state and local applicable regulations.

If this product is mixed with other wastes, the original waste product code may no longer apply and the appropriate code should be assigned.

Dispose of containers contaminated by the product in accordance with local or national legal provisions. For further information, contact your local waste authority.

Special precautions:

This material and its container must be disposed of in a safe way. Care should be taken when handling untreated empty containers.

Avoid dispersal of spilled material and runoff and contact with soil, waterways, drains and sewers.

Empty containers or liners may retain some product residues. Do not re-use empty containers.

Mannington Performance Urethane

SECTION 14: TRANSPORT INFORMATION

- 14.1. In Accordance with DOT Not regulated for transport
14.2. In Accordance with IMDG Not regulated for transport
14.3. In Accordance with IATA Not regulated for transport

SECTION 15: REGULATORY INFORMATION

15.1. US Federal Regulations

This Safety Data Sheet has been prepared according to the Hazard Communication Standard 2024 (HCS 2024)

TSCA - Toxic Substances Control Act

All the components are listed on the TSCA inventory

TSCA listed substances:

calcium oxide; quicklime is listed in TSCA Section 8b

4-methylbenzenesulfonyl isocyanate; 4-isocyanatosulphonyltoluene is listed in TSCA Section 8b

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- is listed in TSCA Section 8b Section 8a - PAIR Section 5

silica sand; quartz is listed in TSCA Section 8b

SARA - Superfund Amendments and Reauthorization Act

Section 302 - Extremely Hazardous Substances:

No substances listed

Section 304 - Hazardous substances:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

Section 313 - Toxic chemical list:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-

CERCLA - Comprehensive Environmental Response, Compensation, and Liability Act

Substance(s) listed under CERCLA:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- Reportable quantity: 5000 pounds

CAA - Clean Air Act

CAA listed substances:

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- is listed in CAA Section 112(b) - HAP Section 112(b) - HON

CWA - Clean Water Act

CWA listed substances:

No substances listed

USA - State specific regulations

California Proposition 65

Substance(s) listed under California Proposition 65:

silica sand; quartz Listed as carcinogen

Massachusetts Right to know

Substance(s) listed under Massachusetts Right to know:

calcium oxide; quicklime

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato- silica sand; quartz

Mannington Performance Urethane

Pennsylvania Right to know

Substance(s) listed under Pennsylvania Right to know:

calcium oxide; quicklime

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-silica sand; quartz

New Jersey Right to know

Substance(s) listed under New Jersey Right to know:

calcium oxide; quicklime

4,4'-methylenediphenyl diisocyanate; benzene, 1,1'-methylenebis[4-isocyanato-silica sand; quartz

Canada - Federal regulations

DSL - Domestic Substances List

All the substances are listed in the DSL.

NDSL - Non Domestic Substances List

This product complies with NDSL inventory

NPRI - National Pollutant Release Inventory

NPRI (National Pollutant Release Inventory) - List of substances listed.

No substances listed

SECTION 16: OTHER INFORMATION, INCLUDING DATE OF PREPARATION OR LAST REVISION

Revision Date : 3/18/2026

Reasonable care has been taken in the preparation of this information, but the manufacturer makes no warranty of merchantability or any other warranty, expressed or implied, with respect to this information. The manufacturer makes no representations and assumes no liability for any direct, incidental or consequential damages resulting from its use. The information herein is presented in good faith and believed to be accurate as of the effective date given. It is the buyer's responsibility to ensure that its activities comply with Federal, State or provincial, and local laws.

This document was prepared by a competent person who has received appropriate training.

It is the duty of the user to ensure that this information is appropriate and complete with respect to the specific use intended.

This SDS cancels and replaces any preceding release.

Code	Description
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H318	Causes serious eye damage.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H334	May cause allergy or asthma symptoms or breathing difficulties if inhaled. H335 May cause respiratory irritation.
H350	May cause cancer.
H351	Suspected of causing cancer.
H372	Causes damage to organs through prolonged or repeated exposure.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.

Mannington Performance Urethane

Code	Hazard class and hazard category	Description
A.1/4/Inhal	Acute Tox. 4	Acute toxicity (inhalation), Category 4
A.2/2	Skin Irrit. 2	Skin irritation, Category 2
A.3/1	Eye Dam. 1	Serious eye damage, Category 1
A.3/2A	Eye Irrit. 2A	Eye irritation, Category 2A
A.4.1/1	Resp. Sens. 1	Respiratory Sensitization, Category 1
A.4.2/1	Skin Sens. 1	Skin Sensitization, Category 1
A.6/1A	Carc. 1A	Carcinogenicity, Category 1A
A.6/2	Carc. 2	Carcinogenicity, Category 2
A.8/3	STOT SE 3	Specific target organ toxicity following single exposure, Category 3
A.9/1	STOT RE 1	Specific target organ toxicity following repeated exposure, Category 1
A.9/2	STOT RE 2	Specific target organ toxicity following repeated exposure, Category 2

Legend to abbreviations and acronyms used in the safety data sheet:

ADR: European Agreement concerning the International Carriage of Dangerous Goods by Road.

RID: Regulation Concerning the International Transport of Dangerous Goods by Rail.

IMDG: International Maritime Code for Dangerous Goods.

IATA: International Air Transport Association.

IATA-DGR: Dangerous Goods Regulation by the "International Air Transport Association" (IATA).

ICAO: International Civil Aviation Organization.

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO).

GHS: Globally Harmonized System of Classification and Labeling of Chemicals.

CLP: Classification, Labeling, Packaging.

EU CLP Index: Index number as reported in Annex VI to EU Reg. 1272/2008

EINECS: European Inventory of Existing Commercial Chemical Substances.

INCI: International Nomenclature of Cosmetic Ingredients.

CAS: Chemical Abstracts Service (division of the American Chemical Society).

GefStoffVO: Ordinance on Hazardous Substances, Germany.

LC50: Lethal concentration, for 50 percent of test population.

LD50: Lethal dose, for 50 percent of test population.

DNEL: Derived No Effect Level.

PNEC: Predicted No Effect Concentration.

TLV: Threshold Limiting Value.

TWATLV: Threshold Limit Value for the Time Weighted Average 8 hour day. (ACGIH Standard).

STEL: Short Term Exposure limit.

STOT: Specific Target Organ Toxicity. WGK: German

Water Hazard Class. KSt: Explosion coefficient.