

Teles® Collection

Style	Teles® Tile & Plank
Construction	High Resiliency Thermoset Rubber Plank & Tile
Classification	ASTM F1344 Type 1 (B), Grade 1
Total Thickness	1/8" (3.2 mm)
Profile	Smooth
Sizes	35" x 35" (889 mm x 889 mm), 17.5" x 35" (445 mm x 889 mm), 17.5" x 17.5" (445 mm x 445 mm), 5.8" x 35" (148 mm x 889 mm))
Colors	15
Packaging	35" x 35" - Individual Pieces 17.5" x 35" - 10 pcs, 42.6 ft2 (3.958 m2), 40.8 lbs (18.51 kg) 17.5" x 17.5" - 20 pcs, 42.6 ft2 (3.958 m2), 40.9 lbs (18.6 kg) 5.8" x 35" - 25 pcs, 35.5 ft2 (3.298 m2), 34 lbs (15.42 kg)
Adhesive	Porous & Non-porous Substrates: MR-911 Full Spread, General Purpose Acrylic Note: Must use QuickStix under hospital beds and heavy rolling loads or where high performance is needed.

Testing	
HUD/FHA	Meets or Exceeds
ADAG (American Disability Act Guidelines)	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.15%
Squareness (ASTM F2055)	Passes - Max 0.010" (Tile)
Squareness (ASTM 2421)	Passes - Max 0.010" (Plank)
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 1,500 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel (ASTM E648) Smoke Density (ASTM E662)	Passes - Class 1; ≥ 0.45 watts/cm2 Passes - < 450
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514) Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - < 8 Delta E Color Change Passes - No More Than Slight Change Dimensional Stability (Aachen Test)
Environmental Data	

Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
Product Declarations	EPD
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials
mindful MATERIALS Manufacturing	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information Calhoun, GA (USA) - ISO 14001 Certified

Warranty	
	Limited 10 Year Commercial Warranty Limited 10 Year Wear Warranty

Crafted with Purpose