

Spacia® Xpress: 5.0 mm

Style	Abstract: 5.0 mm	Stone: 5.0 mm	Wood: 5.0 mm
Construction	Luxury Vinyl Tile Non-ortho Phthalate	Luxury Vinyl Tile Non-ortho Phthalate	Luxury Vinyl Tile Non-ortho Phthalate
Classification	ASTM F1700 Class III, Type B	ASTM F1700 Class III, Type B	ASTM F1700 Class III, Type B
Total Thickness Wear	0.197" (5.0 mm)	0.197" (5.0 mm)	0.197" (5.0 mm)
Layer Thickness Wear	20 mil (0.51 mm)	20 mil (0.51 mm)	20 mil (0.51 mm)
Layer	Quantum Guard Elite®	Quantum Guard Elite®	Quantum Guard Elite®
Edge Treatment Sizes	Micro-bevel 7.25" x 48" (184 x 1219 mm) 18" x 18" (457 x 457 mm) Sizes are style dependent; refer to Product Availability Chart	Micro-bevel 18" x 18" (457 x 457 mm)	Micro-bevel 7.25" x 48" (184 x 1219 mm)
Colors	5	5	10
Packaging	7.25" x 48" - 9 pcs, 21.75 ft ² (2.02 m ²), 38.06 lbs (17.26 kg) 18" x 18" - 10 pcs, 22.5 ft ² (1.254 m ²), 39.375 lbs (10.72 kg)	18" x 18" - 10 pcs, 22.5 ft ² (1.254 m ²), 39.375 lbs (10.72 kg)	7.25" x 48" - 9 pcs, 21.75 ft ² (2.02 m ²), 38.06 lbs (17.26 kg)
Adhesive	Porous & Non-porous Substrates: V-88 Transitional Adhesive MoistureLoc Full Spread, One Component V-95 Full Spread, 2-part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray Note: Must use V-95, MoistureLoc or XpressStep adhesive under hospital beds and heavy rolling load areas. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95 or MoistureLoc should be used.		
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.		
Testing	HUD/FHA Flexibility (ASTM F137) Dimensional Stability (ASTM F2199) Squareness (ASTM F2055) Static Load (ASTM F970 mod.) Residual Indentation (ASTM F1914) Flooring Radiant Panel (ASTM E648) Smoke Density (ASTM E662) Slip Resistance (ASTM C1028) Resistance to Light (ASTM F1515) Chemical Resistance (ASTM F925) Resistance to Heat (ASTM F1514)		
Environmental Data	Passes Passes - 1" Mandrel - No Crack/Break Passes - Max 0.020 in/in ft Passes - Max 0.010" Passes - 2,000 PSI; Residual Indent ≤ 0.005" Passes - < 8% Avg; 10% Single Value Passes - Class 1; ≥ 0.45 watts/cm ² Passes - ≤ 450 Passes - ≥ 0.5 Leather; 0.6 Rubber Passes Passes Passes		
Rapidly Renewable Content	Contains 2% rapidly renewable resource content		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017		
Product Declarations	Third Party Verified EPD, HPD		
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information		
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EDPs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials		
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information		
Manufacturing	Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl Verified Silver		
Warranty	Limited 15-Year Commercial Warranty Limited 15-Year Quantum Guard Elite® Wear Warranty		