

Color Anchor LVT Collection

| Style | Groove, Stride |
|------------------------------------|---|
| Construction | Luxury Vinyl Tile Non-ortho Phthalate |
| Classification | ASTM F1700 Class III, Type B |
| Total Thickness | 0.098" (2.5 mm) |
| Wear Layer Thickness | 20 mil (0.51 mm) |
| Wear Layer | Quantum Guard Elite® |
| Edge Treatment | Bevel or Unbevel |
| Sizes | 6" x 36" (152 x 915 mm) 12" x 24" (305 x 610 mm) 18" x 18" (457 x 457 mm) |
| Colors | 29 colors per style |
| Packaging | 6" x 36" - 30 pcs, 45 ft ² (4.181 m ²), 33.53 lbs (15.21 kg) 12" x 24" - 18 pcs, 36 ft ² (3.345 m ²), 26.82 lbs (12.17 kg) 18" x 18" - 12 pcs, 27 ft ² (2.508 m ²), 20.12 lbs (9.126 kg) Packaging may differ for QuickStix® |
| Adhesive | Porous & Non-porous Substrates: V-88 Full Spread MoistureLoc Full Spread, One Component V95 Full Spread, 2-part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray Note: Must use V-95, MoistureLoc, or XpressStep adhesive under stationary heavy point loads. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95 or MoistureLoc should be used. |
| QuickStix® | Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas. |
| Installation Method | All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate. |
| Testing | |
| HUD/FHA | Passes |
| Flexibility (ASTM F137) | Passes - 1" Mandrel - No Crack/Break |
| Dimensional Stability (ASTM F2199) | Passes - Max 0.020 in/lin ft |
| Squareness (ASTM F540) | Passes - Max 0.010" |
| Static Load (ASTM F970 mod.) | Passes - 2,000 PSI; Residual Indent ≤ 0.005" |
| Residual Indentation (ASTM F1914) | Passes - < 8% Avg / 10% Single Value |
| Flooring Radiant Panel (ASTM E648) | Passes - Class 1; ≥ 0.45 watts/cm ² |
| Smoke Density (ASTM E662) | Passes - ≤ 450 |
| Slip Resistance (ASTM C1028) | Passes - ≥ 0.5 Leather; 0.6 Rubber |
| Resistance to Light (ASTM F1515) | Passes |
| Chemical Resistance (ASTM F925) | Passes |
| Resistance to Heat (ASTM F1514) | Passes |
| Environmental Data | |
| Rapidly Renewable Content | Contains 2% rapidly renewable resource content |
| Indoor Air Quality | FloorScore Certified; CDPH v1.2-2017 |
| Product Declarations | Third Party Verified EPD, HPD |
| Carbon Offset | 105% (Cradle to Gate (A1-A3); visit website for more information |
| LEED | May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials |
| mindful MATERIALS Manufacturing | Visit mindfulmaterials.com for current transparency information Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl™ Verified Silver |
| Warranty | |
| | Limited 15-Year Commercial Warranty Limited 15-Year Quantum Guard Elite® Wear Warranty |