

**TX:Style Collection**

<b>Style</b>	<b>A La Mode (Modular)</b>	<b>Bark II (Modular)</b>
<b>Construction</b>	Patterned Loop	Tip-Sheared Patterned Loop
<b>Face Fiber</b>	Type 6,6 Nylon	Type 6,6 Nylon
<b>Dye Method</b>	Yarn/Solution	Yarn/Solution
<b>Gauge</b>	5/64	5/64
<b>Stitches Per Inch</b>	10.66 (41.97 per 10cm)	11.5 (45.28 per 10cm)
<b>Density</b>	5,781 (214.81 kg/m <sup>3</sup> )	6,646 (246.95 kg/m <sup>3</sup> )
<b>Pile Thickness</b>	0.137" (3.48 mm)	0.130" (3.30 mm)
<b>Weight</b>	22 oz/yd <sup>2</sup> (746 g/m <sup>2</sup> )	24 oz/yd <sup>2</sup> (814 g/m <sup>2</sup> )
<b>Backing Type</b>	Infinity® 2 Modular rEvolve II Modular	Infinity® 2 Modular rEvolve II Modular
<b>Size</b>	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
<b>Colors</b>	16	16
<b>Packaging</b>	8 yd <sup>2</sup> / 18 Tiles	8 yd <sup>2</sup> / 18 Tiles
<b>Adhesive</b>	Infinity 2 Adhesive XpressStep Spray FreLock Tabs -Infinity 2 Modular only	Infinity 2 Adhesive XpressStep Spray FreLock Tabs - Infinity 2 Modular only
<b>Installation Method</b>	Vertical Ashlar	Horizontal Brick Ashlar
<b>Testing</b>		
<b>Dimensional Stability (Aachen Test)</b>	Passes	Passes
<b>Electrostatic Propensity (AATCC 134)</b>	Less than 3.0 KV	Less than 3.0 KV
<b>Flooring Radiant Panel (ASTM E648)</b>	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
<b>Smoke Density (ASTM E662)</b>	≤ 450-Passes	≤ 450-Passes
<b>Methenamine Pill Test (ASTM D2859)</b>	Passes	Passes
<b>Hexapod (ASTM D5252) TARR</b>	3.5	3.5
<b>Environmental Data</b>		
<b>NSF/ANSI 140 Certification</b>	Infinity® 2 Modular - Gold / rEvolve II Modular -Gold	
<b>Recycled Content</b>	Contains Recycled Content	
<b>Indoor Air Quality</b>	CRI Green Label Plus Certified	
<b>Product Declarations</b>	Third Party Verified EPD, HPD	
<b>LEED</b>	May contribute to LEED Credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
<b>mindful MATERIALS</b>	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information.	
<b>Manufacturing</b>	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.

**TX:Style Collection**

Style	Canopy II (Modular)	Squareberry II (Modular)
Construction	Patterned Loop	Tip-Sheared Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Yarn/Solution	Yarn/Solution
Gauge	5/64	5/64
Stitches Per Inch	12.33 (48.54 per 10cm)	12 (47.24 per 10cm)
Density	6,711 (249.37 kg/m <sup>3</sup> )	6,133 (227.89 kg/m <sup>3</sup> )
Pile Thickness	0.118" (3.00 mm)	0.135" (3.43 mm)
Weight	22 oz/yd <sup>2</sup> (746 g/m <sup>2</sup> )	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )
Backing Type	Infinity <sup>®</sup> 2 Modular rEvolve II Modular	Infinity <sup>®</sup> 2 Modular rEvolve II Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	16	16
Packaging	8 yd <sup>2</sup> / 18 Tiles	8 yd <sup>2</sup> / 18 Tiles
Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs-Infinity 2 modular only	Infinity 2 Adhesive XpressStep Spray FreLock Tabs-Infinity 2 modular only
Installation Method	Horizontal Brick Ashlar	Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 KV	Less than 3.0 KV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	4
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	Infinity <sup>®</sup> 2 Modular - Gold / rEvolve II Modular -Gold	
Recycled Content	Contains Recycled Content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
LEED	May contribute to LEED Credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information.	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double dark or double-light lines at the seam and to some extent, pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.

**TX:Style Collection**

Style	Bark II (Broadloom)	Canopy II (Broadloom)	Squareberry II (Broadloom)
<b>Construction</b>	Tip-Sheared Patterned Loop	Patterned Loop	Tip-Sheared Patterned Loop
<b>Face Fiber</b>	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
<b>Dye Method</b>	Yarn/Solution	Yarn/Solution	Yarn/Solution
<b>Gauge</b>	5/64	5/64	5/64
<b>Stitches Per Inch</b>	11.5 (45.28 per 10cm)	12.33 (48.54 per 10cm)	12 (47.24 per 10cm)
<b>Density</b>	6,646 (246.95 kg/m <sup>3</sup> )	6,711 (249.37 kg/m <sup>3</sup> )	6,133 (227.89 kg/m <sup>3</sup> )
<b>Pile Thickness</b>	0.130" (3.30 mm)	0.118" (3.00 mm)	0.135" (3.43 mm)
<b>Weight</b>	24 oz/yd <sup>2</sup> (814 g/m <sup>2</sup> )	22 oz/yd <sup>2</sup> (746 g/m <sup>2</sup> )	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )
<b>Backing Type</b>	UltraBac® RE, Integra® HP	UltraBac® RE, Integra® HP	UltraBac® RE, Integra® HP
<b>Size</b>	12' 6" Width	12' 6" Width	12' 6" Width
<b>Colors</b>	16	16	16
<b>Pattern Repeat</b>	18 3/4" W x 21 1/4" L	18 3/4" W x 42 1/4" L	18 3/4" W x 19 1/2" L
<b>Adhesive</b>	Ultra Adhesive Integra-2 Adhesive	Ultra Adhesive Integra-2 Adhesive	Ultra Adhesive Integra-2 Adhesive
<b>Testing</b>			
<b>Dimensional Stability (Aachen Test)</b>	Passes	Passes	Passes
<b>Electrostatic Propensity (AATCC 134)</b>	Less than 3.0 KV	Less than 3.0 KV	Less than 3.0 KV
<b>Flooring Radiant Panel (ASTM E648)</b>	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)
<b>Smoke Density (ASTM E662)</b>	≤ 450-Passes	≤ 450-Passes	≤ 450-Passes
<b>Methenamine Pill Test (ASTM D2859)</b>	Passes	Passes	Passes
<b>Hexapod (ASTM D5252) TARR</b>	3.5	3.5	3.5
<b>Environmental Data</b>			
<b>NSF/ANSI 140 Certification</b>	UltraBac® RE - Gold Integra® HP - Gold		
<b>Recycled Content</b>	Contains Recycled Content		
<b>Indoor Air Quality</b>	CRI Green Label Plus Certified		
<b>Product Declarations</b>	Third Party VerifiedEPD, HPD		
<b>LEED</b>	May contribute to LEED Credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
<b>mindful MATERIALS</b>	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information.		
<b>Manufacturing</b>	Calhoun, Georgia (USA) - ISO 14001 Certified		
<b>Warranty</b>			
	Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.