

Style	ColorFields Tile	ColorFields Sheet
Construction	Thermoset Rubber Floor Tile	Thermoset Rubber Sheet Flooring without Backing
Classification	ASTM F1344 Type 1 (B), Grade 1	ASTM F1859, Type 1
Total Thickness	0.118" (3 mm)	0.118" (3 mm)
Profile	Smooth	Smooth
Sizes	24" x 24" (610 x 610 mm)	4' x 49.2' (1.2 x 15 m) Sheet (Full rolls only)
Colors	21	21
Packaging	20 pcs, 80 ft ² (7.432 m ²), 78 lbs (35.38 kg)	196.85 ft ² (18.28 m ²)/roll, 191.49 lbs (86.86 kg)/roll
Adhesive	MR-721 Epoxy Adhesive MR-725 Polyurethane Adhesive MR-911 Acrylic Adhesive	MR-721 Epoxy Adhesive MR-725 Polyurethane Adhesive MR-911 Acrylic Adhesive
Seam Method	N/A	Mannington Commercial Weld Rods

Testing

HUD/FHA	Meets / Exceeds
ADAG (American Disability Act Guidelines)	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.15%
Squareness (ASTM F2055)	Passes - 0.010" Max (Tile)
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 1,200 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - < 450
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change

Environmental Data

Rapidly Renewable	Contains 6% rapidly renewable resource content FloorScore Certified; CDPH v1.2-2017
Content Indoor Air Quality	May contribute to LEED credits:
LEED Scoreboard	Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials.
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information
Manufacturing	Taiwan

Warranty

Limited 10 Year Commercial Warranty
 Limited 10 Year Wear Warranty

Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit manningtoncommercial.com