

Glitch Art Collection

Style	Circuit (Modular)	Cross Talk (Modular)	Hub (Modular)
Construction	Patterned Loop	Patterned Loop	Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	10.66 (41.97 per 10 cm)	9.83 (38.70 per 10 cm)	9.83 (38.70 per 10 cm)
Density	6,667 (247.73 kg/m ³)	6,667 (247.73 kg/m ³)	6,667 (247.73 kg/m ³)
Pile Thickness	0.108" (2.74 mm)	0.108" (2.74 mm)	0.108" (2.74 mm)
Weight	20 oz/yd ² (678 g/m ²)	20 oz/yd ² (678 g/m ²)	20 oz/yd ² (678 g/m ²)
Backing Type	Infinity® 2 Modular	Infinity® 2 Modular	Infinity® 2 Modular
Width	24" x 24" (60.69 x 60.69 cm)	24" x 24" (60.69 x 60.69 cm)	24" x 24" (60.69 x 60.69 cm)
Colors	12	12	12
Packaging	8 yd ² / 18 Tiles	8 yd ² / 18 Tiles	8 yd ² / 18 Tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
Installation Method	Horizontal Brick Ashlar	Horizontal Brick Ashlar	Horizontal Brick Ashlar

Testing

Dimensional Stability (Aachen Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1 ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	3.5 - severe

Environmental Data

NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	Third Party Verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered

Warranty

Limited Lifetime Wear & Backing Warranty
 Limited 15-Year XGUARD® Stain Resistant Warranty
 Limited 15-Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Glitch Art Collection

Style	Mainboard (Modular)	Circuit (Broadloom)
Construction	Patterned Loop	Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	9.5 (37.40 per 10 cm)	10.66 (41.97 per 10 cm)
Density	6,667 (247.73 kg/m ³)	6,667 (247.73 kg/m ³)
Pile Thickness	0.108" (2.74 mm)	0.108" (2.74 mm)
Weight	20 oz/yd ² (678 g/m ²)	20 oz/yd ² (678 g/m ²)
Backing Type	Infinity® 2 Modular	UltraBac® RE, Integra HP®
Size	24" x 24" (60.69 x 60.69 cm)	12'6" (3.81 m)
Colors	12	12
Pattern Repeat	N/A	18 3/4" W x 19 1/2" L
Packaging	8 yd ² / 18 Tiles	N/A
Adhesive	Infinity 2 Adhesive	M-Guard Ultra Adhesive Integra 2 Adhesive
Installation Method	Herringbone, Horizontal Brick Ashlar, Vertical Ashlar	N/A
Testing		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1 ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.5 - severe	
Environmental Data		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, UltraBac® RE - Gold, Integra® HP - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.