

Specification

## Edge Guard Seam Sealer Specification

### DESCRIPTION

Edge Guard seam sealer is solvent, high strength seam sealer for eliminating seam raveling when used with Mannington's latex and polyurethane carpet backings. Edge Guard is the appropriate seam sealer for Mannington's UltraBac RE and DeltaLoc backing systems.

### FEATURES

- Easy Application
- No Solvents
- Low VOC's
- Non-Flammable
- CRI Green Label Certified

### INSTALLATION

Seal seam the edge by applying a 1/8" bead of Edge Guard. The sealer should be applied so that it encapsulates the base of the yarn tufts, the primary and secondary backing. Place breadth of the carpet into position and work seam with slight compression ensuring seam sealer transfer. Roll opposite breadth forcing air pockets out away from the seam. Clean away any excess adhesive that may have wicked up through the seam. Continue these techniques throughout remainder of installation.

### COVERAGE

8 oz bottle approximately 100 sq. yd or 100 Lft.

32 oz bottle approximately 400 sq. yd or 400 Lft.

### PACKAGING

**Size** 6 – 8 oz bottles / 4 – 32 oz bottles

**Order Code** 147599 / 147600

**Weight** 4 lbs. case / 10 lbs. case.

### STORAGE

Store in climate controlled interior locations only between 50 - 90°F. Protect from freezing. Edge Guard has a two-year shelf life on unopened containers.

### CLEAN UP

Wet sealer should be cleaned immediately with water for removal.

### WARRANTY

Edge Guard Seam Sealer is manufactured according to exacting quality control standards specifically for the installation of Mannington's UltraBac RE woven synthetic and DeltaLoc cushion backed carpet. Edge Guard Seam Sealer is warranted to be free from manufacturing defects for two years.