



ColorFields®

Mannington
COMMERCIAL



Cover: ColorFields® - Sonic 896, Cadet 881, Fallow 885, Battleship 858
Above: ColorFields® - Sonic 896, Lupine 888, Moraine 890; BurkeBase® - Horizon 920



ColorFields® - Sonic 896, Lupine 888, Moraine 890
BurkeBase® - Horizon 920



ColorFields® - Scroll 895, Warm White 899, Mesa 889, Laurel Green 887
BurkeBase® - Nutmeg 509

Style	ColorFields Tile	ColorFields Sheet
Construction	Thermoset Rubber Floor Tile	Thermoset Rubber Sheet Flooring without Backing
Classification	ASTM F1344 Type 1 (B), Grade 1	ASTM F1859, Type 1
Total Thickness	0.118" (3 mm)	0.118" (3 mm)
Profile	Smooth	Smooth
Sizes	24" x 24" (610 x 610 mm)	4' x 49.2' (1.2 x 15 m) Sheet (Full rolls only)
Colors	21	21
Packaging	20 pcs, 80 ft ² (7.432 m ²), 78 lbs (35.38 kg)	196.85 ft ² (18.28 m ²)/roll, 191.49 lbs (86.86 kg)/roll
Adhesive	MR-721 Epoxy Adhesive MR-725 Polyurethane Adhesive MR-911 Acrylic Adhesive	MR-721 Epoxy Adhesive MR-725 Polyurethane Adhesive MR-911 Acrylic Adhesive
Seam Method	N/A	Mannington Commercial Weld Rods

Testing

HUD/FHA	Meets / Exceeds
ADAG (American Disability Act Guidelines)	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.15%
Squareness (ASTM F2055)	Passes - 0.010" Max (Tile)
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 1,200 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - < 450
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change

Environmental Data

Rapidly Renewable	Contains 6% rapidly renewable resource content FloorScore Certified; CDPH v1.2-2017
Content Indoor Air Quality	May contribute to LEED credits:
LEED Scoreboard	Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials.
mindful MATERIALS	Visit mM Origin website, mindfulmaterials.origin.build , for current transparency information
Manufacturing	Taiwan

Warranty

Limited 10 Year Commercial Warranty
 Limited 10 Year Wear Warranty