

**SUNDRIES**

Updated: 1/26/2024

**RESILIENT SHEET**

**Trowel Adhesives**

Product Description	Container Size	SAP Code	Order Code	PH	Intact Vapor Barrier*	No Vapor Barrier			Coverage - SF per Container		Product Applications	Trowel / Installation
					RH%	MVER/ lbs.	pH	Porous	Non-Porous	Shelf Life		
M-Guard V-88 Sheet	1 Gallon	295457	804588	95% RH 10 MVER 12 PH	90%	10	12	250	350	1 Year	Assurance III, BioSpec Armor/MD/SR, Bloom, City Hub, Color Anchor, Discovery, Entwined, Paradigm II, & Realities III	1/16 x 1/32 x 5/64 "U" Notch - Non-porous
	4 Gallon	186054	802387					1,000 (4)	1400 (4)			1/16 x 1/32 x 1/32 "U" Notch - Porous
MoistureLoc Sheet	2 Gallon	454730	805159	(Porous)	95%	10	12	500	-	1 Year	Assurance III, BioSpec Armor/MD/SR, Bloom, City Hub, Color Anchor, Discovery, Entwined, Paradigm II, & Realities III - For heavy rolling load areas or where higher risk of topical moisture would be a concern.	1/16 x 1/32 x 1/32 "U" Notch - Porous
				(Non-Porous)	95%	10	12	-	500			1/16 x 1/32 x 1/32 "U" Notch - Non- Porous

\*No moisture testing required when class B minimum, intact moisture vapor barrier is present. pH testing required where specified. Slabs must be at least 45 days old.

Product Description	Container Size	SAP Code	Order Code	RH%	MVER/ lbs	pH	Porous	Non-Porous	Shelf Life	Product Applications	Trowel / Installation
V-95 (2 Part Epoxy)	1 Gallon	457153	800291	85%	5	9	185-245	-	1 Year	Assurance III, BioSpec MD/RE/SR, Bloom, City Hub, Color Anchor, Discovery, Entwined, Paradigm II, Realities III, & all LVT - For heavy rolling load areas or where higher risk of topical moisture would be a concern.	1/16 x 1/32 x 1/32 "U" Notch - Porous
MR-710 (Single Part Urethane)	2 Gallon	443839	R710G2	90%	8	9	190 SF/2-Gallon	-	1 Year	Attune Collection; Reset recycled sports flooring, tile and sheet	1/16 x 1/16 x 1/16 "Square" Notch - Porous

**Spray Adhesive**

Product Description	Container Size	SAP Code	Order Code	RH%	MVER/ lbs	pH	Coverage - SF per Container		Shelf Life	Product Applications	Trowel / Installation
							Porous	Non-Porous			
XpressStep for LVT/Sheet/Carpet (Sheet Info)	6 Cans/Car 6 Cans/Car WINTERPACK	291548 391480	700116 800005	95%	8	11	150/Can	185/Can	3 Years	For immediate use and heavy rolling loads, Winter packs to be used October 1 - April 15	Shake well prior to use, spray while walking slowly, do not use sweeping arm motion

**Seam Sealers & Welds**

Product Description	Container Size	SAP Code	Order Code	Coverage	Product Applications	Description
MCS-42 Seam Sealer	1 Pint	186836	849842	400-600 lineal feet/pint	BioSpec Armor/MD, Color Anchor Prism & Terrene	For all sheet goods except urethane-based wear layers (see below)
MLG-33 Urethane Sealer	1 oz Can	186873	832233	70 lineal feet/kit	Assurance III, Bloom, City Hub, Biospec SR, Color Anchor Arc, Entwined, Insight Plus, Insight Plus GB, Realities III, & Paradigm	2-part sealer for urethane wear layers
VST-96	1 Bottle	186871	832204	4 oz bottle; as needed	Used with seam sealers above	Bottle for MCS42 Seam Sealer
Weld Rod - Sheet Standard 4 mm Custom 6 mm	Spool	Various	Various	165 lf/spool 100 lf/spool	For Heat Welding All Commercial Sheet Vinyl or Commercial Sheet Vinyl to IdealBase	Preferred commercial installation method
QGE Seam Coater Pen	1 Pen	288566	801503	300 lineal feet per pen	All Commercial Sheet Vinyl; Attune Collection	High quality acrylic floor finish & urethane coating that is easily applied. *DO NOT OVER APPLY ONTO THE QG TECHNOLOGY WEAR LAYER OF SHEET VINYL.*

\*No moisture testing required when class B minimum, intact moisture vapor barrier is present. pH testing required where specified. Slabs must be at least 45 days old. No standing water, no free liquids present, no evidence of moisture staining, no hydrostatic pressure

**SUNDRIES**

Updated: 1/26/2024

**RESILIENT SHEET**

QuickStix					With Moisture Resistant Primer	With Premium Universal Primer			Coverage - SF per Container		Product Applications	Trowel / Installation
					RH%	MVER/ lbs	pH	Porous	Non-Porous	Shelf Life		
Product Description	Container Size	SAP Code	Order Code	PH	RH%	MVER/ lbs	pH	Porous	Non-Porous	Shelf Life	Product Applications	Trowel / Installation
QuickStix for Sheet Universal Primer <i>(Includes Universal Primer)</i>	100 SY Minimum	Various	Various	12	95%	10	12	-	-	18 months	Optional for All Sheet Products	High moisture peel and stick - must have vapor retarder, 100 SY minimum

*\*\*Moisture Resistant Primer*

Product Description	Container Size	SAP Code	Order Code	Coverage	Product Applications	Description
Premium Universal Primer <i>(Automatically ships with Quickstix Sheet Products)</i>	1 Gallon	293552	804560	350-400 SF per gallon	Optional for All Products except QuickStix, Required for QuickStix	Medium nap paint roller. For large jobs, apply with garden sprayer, airless rig or regular paint sprayer. Primer/pH Blocker/Neutralize Alkali /Integra HP/Installations specific to FreLock Tabs
	4 Gallon	293549	804558			

Underlayment (Attune Only)									
Product Description	Container Size	SAP Code	Order Code	RH%	MVER/ lbs	pH	Coverage - FT <sup>2</sup> /Roll	Product Applications	Description
Attune Sound Control Underlayment (Rubber backing only)	1 Roll / 120 SF (48" x 30')	543192	SCU100	-	-	-	120	Use when installing IdealBase with Attune Collection	Attune Collection - <b>Required with IdealBase Installation</b>