



Access Collection

Mannington
COMMERCIAL



Cover: Stone - Linear Stone Shale SX5S3606, **Abstract** - Linen Weave SX5A3800,
Wood - Shibori Jasmine SX5W7800
Above: Stone - Linear Stone Black SX5S2405









Wood - Shibori Jasmine SX5W7800



Wood - Black Walnut SX5W2534



Wood - Frosted Oak SX5W5020

Access Collection Product Availability

Product Name	Product Code	Surface Finish	Micro-beveled Edges	5.91" x 39.37" (150.1 x 1000 mm)	17.7" x 17.7" (449.6 x 499.6 mm)
ABSTRACT					
Equator Wave	SX5AEQ39	Ceramic	•		•
Linen Weave	SX5A3800	Ceramic	•		•
Urban Line Felt	SX5A3271	Ceramic	•		•

STONE					
Ceramic Dark	SX5S3566	Ceramic	•		•
Ceramic Ecru	SX5S3592	Ceramic	•		•
Ceramic Flint	SX5S2594	Ceramic	•		•
Ceramic Light	SX5S1565	Ceramic	•		•
Dry Stone Clay	SX5S4435	Ceramic	•		•
Linear Stone Black	SX5S2405	Ceramic	•		•
Linear Stone Shale	SX5S3606	Ceramic	•		•

WOOD					
Ashdown Plum	SX5W8000	Tick	•	•	
Black Walnut	SX5W2534	Tick	•	•	
Bleached Elm	SX5W2516	Tick	•	•	
Dusky Walnut	SX5W2542	Tick	•	•	
Frosted Oak	SX5W5020	Rustic	•	•	
Shadow Oak	SX5W5022	Rustic	•	•	
Shibori Jasmine	SX5W7800	Tick	•	•	
Simple Beech	SX5W5023	Tick	•	•	
Traditional Oak	SX5W2514	Tick	•	•	
Winter Oak	SX5W5021	Rustic	•	•	

Access Collection

Style	Wood	Stone & Abstract
Construction	Luxury Vinyl Tile	Luxury Vinyl Tile
Classification	Non-ortho Phthalate	Non-ortho Phthalate
Total Thickness	ASTM F1700 Class III, Type B	ASTM F1700 Class III, Type B
Wear Layer Thickness	0.197" (5 mm)	0.197" (5 mm)
Wear Layer	20 mil (0.51 mm)	20 mil (0.51 mm)
Edge Treatment	Enhanced Urethane	Enhanced Urethane
Sizes	Micro-bevel	Micro-bevel
Colors	5.91" x 39.37" (150.1 x 1000 mm) (nominal)	17.7" x 17.7" (449.6 mm x 449.6 mm)
Packaging	10	7 - Stone, 3 - Abstract
Adhesive	12 pcs, 19.375 ft ² (1.8 m ²), 36.19 lbs (16.42 kg)	10 pcs, 21.79 ft ² (2.024 m ²), 40.7 lbs (18.46 kg)
	Loose Lay with Perimeter Glue: Amitico Tackifier XpressStep for LVT & Sheet Vinyl Full Coverage Spray Porous & Non-porous Substrates - Fully adhered, Releasable: Amtico Tackifier Porous & Non-porous Substrates - Fully adhered, Permanent V-88 Full Spread MoistureLoc Full Spread, One Component V-95 Full Spread, 2-Part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray Note: Must use V-95, MoistureLoc or XpressStep adhesive under hospital beds and heavy rolling load areas. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95, MoistureLoc or should be used.	
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.	
Testing	HUD/FHA Flexibility (ASTM F137) Dimensional Stability (ASTM F2199) Squareness (ASTM F2055) Static Load (ASTM F970 mod.) Residual Indentation (ASTM F1914) Flooring Radiant Panel (ASTM E648) Smoke Density (ASTM E662) Slip Resistance (ASTM C1028) Acoustic IIC (ASTM E492) Acoustic STC (ASTM E90) Resistance to Light (ASTM F1515) Chemical Resistance (ASTM F925) Resistance to Heat (ASTM F1514)	
	Passes Passes - 1" Mandrel - No Crack/Break Passes - Max 0.020 in/in ft Passes - Max 0.010" Passes - 2,000 PSI; Residual Indent ≤ 0.005" Passes - < 8% Avg / 10 % Single Value Passes - Class 1; ≥ 0.45 watts/cm ² Passes - ≤ 450 Passes - ≥ 0.5 Leather; 0.6 Rubber 6" Concrete with Drop Ceiling 6" Concrete with Drop Ceiling Passes Passes Passes	
Environmental Data	Indoor Air Quality Product Declaration LEED mindful MATERIALS Manufacturing	
	FloorScore Certified; CDPH v1.2-2017 Third Party EPD May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials Visit mindfulmaterials.com for current transparency information South Korea	
Warranty	Limited 10-Year Commercial Warranty	