

**Notable Collection**

<b>Style</b>	<b>Catalyst (Broadloom)</b>	<b>Catalyst (Modular)</b>
Construction	Tip Sheared Patterned Loop	Tip Sheared Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	12 (47.27 per 10cm)	12 (47.27 per 10cm)
Density	6,000 (222.95 Kg/m3)	6,000 (222.95 Kg/m3)
Pile Thickness	0.108" (2.74 mm)	0.108" (2.74 mm)
Weight	18 oz/sq yd (610 g/m2)	18 oz/sq yd (610 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	74" W x 74.66" L (187.96 x 189.64 cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3	3
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

## Notable Collection

Style	Day Dream (Broadloom)	Day Dream (Modular)
Construction	Tip Sheared Patterned Loop	Tip Sheared Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10cm)	10 (39.37 per 10cm)
Density	6,428 (238.85 Kg/m3)	6,428 (238.85 Kg/m3)
Pile Thickness	0.112" (2.84 mm)	0.112" (2.84 mm)
Weight	20 oz/sq yd (678 g/m2)	20 oz/sq yd (678 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	148" W x 75.60" L (378.46 X 190.50 cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3	3
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

**Notable Collection**

<b>Style</b>	<b>Glimpse (Broadloom)</b>	<b>Glimpse (Modular)</b>
Construction	Tip Sheared Patterned Loop	Tip Sheared Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10.5 (41.34 per 10cm)	10.5 (41.34 per 10cm)
Density	6,428 (238.85 Kg/m3)	6,428 (238.85 Kg/m3)
Pile Thickness	0.112" (2.84 mm)	0.112" (2.84 mm)
Weight	20 oz/sq yd (678 g/m 2)	20 oz/sq yd (678 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	148" W x 81" L (378.46 x 205.74 cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

**Notable Collection**

<b>Style</b>	<b>Halcyon (Broadloom)</b>	<b>Halcyon (Modular)</b>
Construction	Tip Sheared Patterned Loop	Tip Sheared Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10cm)	10 (39.37 per 10cm)
Density	6,428 (238.85 Kg/m3)	6,428 (238.85 Kg/m3)
Pile Thickness	0.112" (2.84 mm)	0.112" (2.84 mm)
Weight	20 oz/sq yd (678 g/m2)	20 oz/sq yd (678 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	148" W x 81" L (378.46 x 205.74 cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3	3
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

**Notable Collection**

<b>Style</b>	<b>Harmony (Broadloom)</b>	<b>Harmony (Modular)</b>
Construction	Patterned Loop	Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	12 (47.24 per 10cm)	12 (47.24 per 10cm)
Density	6,230 (231.49 Kg/m3)	6,230 (231.49 Kg/m3)
Pile Thickness	0.104" (2.64 mm)	0.104" (2.64 mm)
Weight	18 oz/sq yd (610 g/m2)	18 oz/sq yd (610 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	74" W x 76.66" L (187.96 x 189.64cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3	3
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

**Notable Collection**

<b>Style</b>	<b>Keepsake (Broadloom)</b>	<b>Keepsake (Modular)</b>
Construction	Tip Sheared Patterned Loop	Tip Sheared Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10cm)	10 (39.37 per 10cm)
Density	6,428 (238.85 Kg/m3)	6,428 (238.85 Kg/m3)
Pile Thickness	0.112" (2.84 mm)	0.112" (2.84 mm)
Weight	20 oz/sq yd (678 g/m2)	20 oz/sq yd (678 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	148" W x 73.8" L (378.46 x 187.45 cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3	3
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

## Notable Collection

Style	Mantra (Broadloom)
Construction	Patterned Loop
Face Fiber	Type 6,6
Dye Method	Solution
Gauge	1/12 (47.24 per 10 cm)
Stitches Per Inch	12.33 (48.54 per 10cm)
Density	6,230 (231.49 Kg/m3)
Pile Thickness	0.104" (2.64 mm)
Weight	18 oz/sq yd (610 g/m2)
Backing Type	UltraBac® RE, Integra® HP
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"
Colors	6
Pattern Repeat	74" W x 54" L (187.96 x 137.16 cm)
Packaging	N/A
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive
Installation Method	N/A
<b>Testing</b>	
Dimensional Stability (Aachen Test)	N/A
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	3.5
<b>Environmental Data</b>	
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	Third Party Verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified
<b>Warranty</b>	
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

## Notable Collection

Style	Muse (Broadloom)	Muse (Modular)
Construction	Tip Sheared Patterned Loop	Tip Sheared Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	12 (47.24 per 10cm)	12 (47.24 per 10cm)
Density	6,000 (222.95 Kg/m3)	6,000 (222.95 Kg/m3)
Pile Thickness	0.108" (2.74 mm)	0.108" (2.74 mm)
Weight	18 oz/sq yd (610 g/m2)	18 oz/sq yd (610 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	74" W x 76.66" L (187.96 x 194.72 cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3	3
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

## Notable Collection

Style	Viewpoint (Broadloom)	Viewpoint (Modular)
Construction	Tip Sheared Patterned Loop	Tip Sheared Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10cm)	10 (39.37 per 10cm)
Density	6,428 (238.85 Kg/m3)	6,428 (238.85 Kg/m3)
Pile Thickness	0.112" (2.84 mm)	0.112" (2.84 mm)
Weight	20 oz/sq yd (678 g/m2)	20 oz/sq yd (678 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	148" W x 97.20" L (378.46 x 246.89 cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3	3
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

**Notable Collection**

<b>Style</b>	<b>Zest (Broadloom)</b>	<b>Zest (Modular)</b>
Construction	Tip Sheared Patterned Loop	Tip Sheared Patterned Loop
Face Fiber	Type 6,6	Type 6,6
Dye Method	Solution	Solution
Gauge	1/12 (47.24 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	12.33 (48.54 per 10cm)	12.33 (48.54 per 10cm)
Density	6,000 (222.95 Kg/m3)	6,000 (222.95 Kg/m3)
Pile Thickness	0.108" (2.74 mm)	0.108" (2.74 mm)
Weight	18 oz/sq yd (610 g/m2)	18 oz/sq yd (610 g/m2)
Backing Type	UltraBac® RE, Integra® HP	Infinity® 2 Modular
Sizes	12' 6" width (3.81m) - Pattern Repeats at 12'3"	12" x 36" (30.48 x 91.44 cm)
Colors	6	6
Pattern Repeat	74" W x 74.61" L (187.96 x 189.51 cm)	N/A
Packaging	N/A	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	UltraBac® RE - Ultra Adhesive Integra® HP - Integra 2 Adhesive	Infinity 2 Adhesive
Installation Method	N/A	Vertical Ashlar, Monolithic, Horizontal Brick Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	N/A	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold, Infinity® 2 Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3); see website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing, Limited 15-Year Xguard Stain Resistant, Limited 15-Year ColorSafe Bleach Resistant,	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262