

Access Collection

Style	Wood	Stone & Abstract
<b>Construction</b>	Luxury Vinyl Tile Non-ortho Phtalate	Luxury Vinyl Tile Non-ortho Phtalate
<b>Classification</b>	ASTM F1700 Class III, Type B	ASTM F1700 Class III, Type B
<b>Total Thickness</b>	0.197" (5 mm)	0.197" (5 mm)
<b>Wear Layer Thickness</b>	20 mil (0.51 mm)	20 mil (0.51 mm)
<b>Wear Layer</b>	Enhanced Urethane	Enhanced Urethane
<b>Edge Treatment</b>	Micro-bevel	Micro-bevel
<b>Sizes</b>	5.91" x 39.37" (150.1 x 1000 mm) (nominal)	17.7" x 17.7" (449.6 mm x 449.6 mm)
<b>Colors</b>	10	7 - Stone, 3 - Abstract
<b>Packaging</b>	12 pcs, 19.375 ft <sup>2</sup> (1.8 m <sup>2</sup> ), 3619 lbs (16.42 kg)	10 pcs, 21.79 ft <sup>2</sup> (2.024 m <sup>2</sup> ), 40.7 lbs (18.46 kg)
<b>Adhesive</b>	<b>Loose Lay with Perimeter Glue:</b> Amitico Tackifier XpressStep for LVT & Sheet Vinyl Full Coverage Spray <b>Porous &amp; Non-porous Substrates - Fully adhered, Releasable:</b> Amtico Tackifier <b>Porous &amp; Non-porous Substrates - Fully adhered, Permanent</b> V-88 Full Spread MoistureLoc Full Spread, One Component V-95 Full Spread, 2-Part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray  Note: Must use V-95, MoistureLoc or XpressStep adhesive under hospital beds and heavy rolling load areas. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95, MoistureLoc or should be used.	
<b>Installation Method</b>	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.	
<b>Testing</b>	HUD/FHA Flexibility (ASTM F137) Dimensional Stability (ASTM F2199) Squareness (ASTM F2055) Static Load (ASTM F970 mod.) Residual Indentation (ASTM F1914) Flooring Radiant Panel (ASTM E648) Smoke Density (ASTM E662) Slip Resistance (ASTM C1028) Acoustic IIC (ASTM E492) Acoustic STC (ASTM E90) Resistance to Light (ASTM F1515) Chemical Resistance (ASTM F925) Resistance to Heat (ASTM F1514)	
<b>Environmental Data</b>	Passes Passes - 1" Mandrel - No Crack/Break Passes - Max 0.020 in/in ft Passes - Max 0.010" Passes - 2,000 PSI; Residual Indent ≤ 0.005" Passes - < 8% Avg / 10 % Single Value Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup> Passes - ≤ 450 Passes - ≥ 0.5 Leather; 0.6 Rubber 6" Concrete with Drop Ceiling 6" Concrete with Drop Ceiling Passes Passes Passes	
<b>Indoor Air Quality Product Declaration LEED</b>	FloorScore Certified; CDPH v1.2-2017 Third Party EPD May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information South Korea	
<b>mindful MATERIALS Manufacturing</b>		
<b>Warranty</b>	Limited 10-Year Commercial Warranty	