

| Style | Stone |
|------------------------------------|--|
| Construction | Luxury Vinyl Tile Non-ortho Phthalate |
| Classification | ASTM F1700 Class III, Type B |
| Overall Thickness | 0.098" (2.5 mm) |
| Wear Layer Thickness | 40 mil (1 mm) |
| Wear Layer | Quantum Guard Elite® |
| Edge Treatment | Micro-beveled or Unbeveled |
| Sizes | 12" x 12" (305 x 305 mm) 12" x 18" (305 x 457 mm) 12" x 24" (305 x 610 mm) 18" x 18" (457 x 457 mm) 18" x 36" (457 x 915 mm) 18" x 48" (457 x 1219 mm) 4" x 36" (102 x 915 mm) 6" x 36" (152 x 915 mm) 6" x 48" (152 x 1219 mm) 9" x 36" (229 x 915 mm) 9" x 48" (229 x 1219 mm) |
| Colors | 35 |
| Packaging | 12" x 12" - 45 pcs, 45 ft2 (4.181 m2), 33.71 lbs (15.29 kg) 12" x 18" - 30 pcs, 45 ft2 (4.181 m2), 33.71 lbs (15.29 kg) 12" x 24" - 20 pcs, 40 ft2 (3.716 m2), 29.96 lbs (13.59 kg) 18" x 18" - 20 pcs, 45 ft2 (4.181 m2), 33.71 lbs (15.29 kg) 18" x 24" - 15 pcs, 45 ft2 (4.181 m2), 30.06 lbs (13.63 kg) 18" x 36" - 11 pcs, 49.5 ft² (4.59 m²), 37.08 lbs (16.82 kg) 18" x 48" - 7 pcs, 42 ft² (3.902 m²), 31.46 lbs (14.27 kg) 4" x 36" - 45 pcs, 45 ft² (4.181 m²), 33.71 lbs (15.29 kg) 6" x 36" - 30 pcs, 45 ft² (4.181 m²), 33.71 lbs (15.29 kg) 6" x 48" - 24 pcs, 48 ft² (4.46 m²), 32.06 lbs (14.54 kg) 9" x 36" - 20 pcs, 45 ft² (4.181 m²), 33.71 lbs (15.29 kg) 9" x 48" - 15 pcs, 45 ft² (4.181 m²), 30.06 lbs (13.63 kg) |
| Adhesive | Packaging may differ for QuickStix® Porous & Non-porous Substrates: V-88 Full Spread MoistureLoc Full Spread, One Component V-95 Full Spread, 2-part Epoxy XpressStep for LVT & Sheet Vinyl Full Coverage Spray Note: Must use V-95, MoistureLoc, or XpressStep adhesive under hospital beds and heavy rolling load areas. In more abusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only V-95RU MoistureLoc should be used. |
| QuickStix® | Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas |
| Installation Method | All arrows in the same direction. Tiles should be installed block or staggered; when quarter turned, arrows should alternate |
| Testing | |
| HUD/FHA | Passes |
| Flexibility (ASTM F137) | Passes - 1" Mandrel - No Crack/Break |
| Dimensional Stability (ASTM F2199) | Passes - Max 0.020 in/in ft |
| Squareness (ASTM F2055) | Passes - Max 0.010" |
| Static Load (ASTM F970 mod.) | Passes - 2,000 PSI; Residual Indent ≤ 0.005" |
| Residual Indentation (ASTM F1914) | Passes - < 8% Avg / 10% Single Value |
| Flooring Radiant Panel (ASTM E648) | Passes - Class 1; ≥ 0.45 watts/cm2 |
| Smoke Density (ASTM E662) | Passes - ≤ 450 |
| Slip Resistance (ASTM C1028) | Passes - ≥ 0.5 Leather; 0.6 Rubber |
| Resistance to Light (ASTM F1515) | Passes |
| Chemical Resistance (ASTM F925) | Passes |
| Resistance to Heat (ASTM F1514) | Passes |
| Environmental Data | |
| Indoor Air Quality | FloorScore Certified; CDPH v1.2-2017 |
| Product Declarations | Third party verified EPD, HPD |
| Carbon Offset | 105% Cradle to Gate (A1-A3), see website for additional information |
| LEED | May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials |
| mindful MATERIALS | Visit mindfulmaterials.com for current transparency information |
| Manufacturing | Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl Verified Silver |
| Warranty | Limited 25-Year Commercial Warranty Limited 25-Year Quantum Guard Elite® Wear Warranty |