

SUNDRIES

Updated: 1/26/2024

LVT

Trowel Adhesives

Product Description	Container Size	SAP Code	Order Code	PH	Intact Vapor Barrier*		No Vapor Barrier			Coverage - SF per Container		Product Applications	Trowel / Installation
					RH%	MVER/lbs	pH	Porous	Non-Porous	Shelf Life			
M-Guard V-88 LVT	1 Gallon 4 Gallon	295457 186054	804588 802387	12	95%	10	12	250 1,000 (4)	350 1400 (4)	1 Year	All LVT	1/16 x 1/32 x 5/64 "U" Notch - Non-porous 1/16 x 1/32 x 1/32 "U" Notch - Porous	
MoistureLoc LVT	2 Gallon	454730	805159	(Porous)	None	None	None	500	-	1 Year	All LVT - For heavy rolling load areas or where higher risk of topical moisture would be a concern.	1/16 x 1/32 x 1/32 "U" Notch - Porous	
				(Non Porous)	95%	10	12	-	500		Heavy rolling loads, higher moisture, single component to replace Urethanes and Epoxies	1/16 x 1/32 x 1/32 "U" Notch - Non-Porous	
Amtico PSA (Transitional Pressure Sensitive)	1 Gallon 4 Gallon	457149 457150	804891 804890	12	95%	10	12	250 1000	350 1400	1 Year	High Moisture/Pressure Sensitive	1/16 x 1/32 x 5/64 "U" Notch - Non-porous	
	V-95 (2 Part Epoxy)	1 Gallon	457153	800291	85%	5	9	185-245	-	1 Year	Assurance III, BioSpec Armor/MD/SR, Bloom, City Hub, Color Anchor, Discovery, Entwined, Paradigm II, Realities III, & all LVT - For heavy rolling load areas or where higher risk of topical moisture would be a concern.	1/16 x 1/32 x 1/32 "U" Notch - Porous	
MT-711 (Acrylic Pressure Sensitive)	1 Gallon 4 Gallon	228857 457180	849889 849886	75%	3	9	150 (1 gal) 600 (4)	-	-	1 Year	Perimeter Glue Installation for <b>No Reservations &amp; Uninterrupted LVT</b> . Requires a 9" to 12" band around the perimeter room and/or every 20 feet thereafter. Allow the MT-711 to dry to a clear tacky film, 30 minutes or longer, before placing the tiles /planks. <b><i>This method should not be used in areas with heavy traffic, rolling loads or in any Commercial application where high performance is needed.</i></b>	16" x 16" x 16" Square-notched Trowel	
	Amtico RP-18	2 Gallon	457148	809241	(Porous)	None	None	None	500	-	1 Year	Heavy rolling loads, higher moisture, single component to replace Urethanes and Epoxies	1/16 x 1/32 x 1/32 "U" Notch - Porous
(Non-Porous)					95%	10	12	-	500	1/16 x 1/32 x 1/32 "U" Notch - Non-Porous			

\*No moisture testing required when class B minimum, intact moisture vapor barrier is present. pH testing required where specified. Slabs must be at least 45 days old. No standing water, no free liquids present, no evidence of moisture staining, no hydrostatic pressure

Product Description	Container Size	SAP Code	Order Code	RH%	MVER/lbs	pH	Porous	Coverage - SF per Container		Shelf Life	Product Applications	Trowel / Installation
								Non-Porous	Shelf Life			
Amtico Tackifier (Access Only)	1 Gallon 4 Gallon	278592 278593	803913 803914	75%	5	10	300 1200	-	-	1 Year	Perimeter pressure sensitive adhesive for approved 4 and 5mm products only	Roller

Spray Adhesive

Product Description	Container Size	SAP Code	Order Code	RH%	MVER/lbs	pH	Coverage - SF per Container		Shelf Life	Product Applications	Trowel / Installation
							Porous	Non-Porous			
XpressStep for LVT/Sheet/Carpet (LVT Info)	6 Cans/CAR 6 Cans/CAR WINTERPACK	291548 391480	700116 800005	98%	10	12	100/Can 125/Can	-	3 Years	For immediate use and heavy rolling loads, Winter Packs used October 1 - April 15	Shake well prior to use, spray while walking slowly, do not use sweeping arm motion

Primer

Product Description	Container Size	SAP Code	Order Code	Coverage	Product Applications	Description
Premium Universal Primer	1 Gallon 4 Gallon	293552 293549	804560 804558	350-400 SF per gallon	Optional for All Products, Required for QuickStix	Medium nap paint roller. For large jobs, apply with garden sprayer, airless rig or regular paint sprayer. Primer/pH Blocker/Neutralize Alkali/Integra HP/Installations specific to

**SUNDRIES**

Updated: 1/26/2024

**LVT**

QuickStix					With Moisture Resistant Primer	With Premium Universal Primer			Coverage - SF per Container		Product Applications	Trowel / Installation
Product Description	Container Size	SAP Code	Order Code	PH	RH%	MVER/ lbs	pH	Porous	Non-Porous	Shelf Life		
QuickStix for LVT	1,400 SF Minimum	Various	Various	12	99% w/MVR 95% wo/MVR	18 w/MVR 10 wo/MVR	12	-	-	18 months	High moisture peel and stick - must have vapor retarder, 1,400 SF minimum	Peel and Stick, 1,400 SF Minimum

\*\*Moisture Resistant Primer

**Underlayment (Acoustical)**

Product Description	Container Size	SAP Code	Order Code	RH%	MVER/ lbs	pH	Coverage - FT2/Roll	Product Applications	Trowel / Installation									
Silent Solution	1 Roll	311027	MSS1	80%	5	-	765	Advanced underlayment system that meets or exceeds IIC Sound Requirements for LVT Products	6' x 127.5' Roll, 195 lbs, must use PSA when using double glue method. 441 PSI tensile strength, 250 PSI static load rating. 1.5 mm thickness <table border="1"> <thead> <tr> <th>Product</th> <th>IIC</th> <th>STC</th> </tr> </thead> <tbody> <tr> <td>Ambico Space 2.5 mm LVT</td> <td>62</td> <td>63</td> </tr> <tr> <td>Ambico Space 2.0 mm LVT</td> <td>60</td> <td>62</td> </tr> </tbody> </table>	Product	IIC	STC	Ambico Space 2.5 mm LVT	62	63	Ambico Space 2.0 mm LVT	60	62
Product	IIC	STC																
Ambico Space 2.5 mm LVT	62	63																
Ambico Space 2.0 mm LVT	60	62																

**Finishing Accessories & Moldings**

Product Description	Container Size	SAP Code	Coverage - FT2/CAR		Product Applications
			BEAD SIZE (INCHES)	LINEAL FT/CARTRIDGE	
Triple Stick Adhesive Tube	29 oz Cartridges	391077	1/8"	355	T-molding, Multipurpose Reducer and End Cap
			3/16"	158	
			1/4"	89	
			5/16"	57	
			3/8"	39	

**Stair Renewal System**

Product Description	Container Size	SAP Code	Coverage - FT2/CAR		Product Applications	Notes
			BEAD SIZE (INCHES)	LINEAL FT/CARTRIDGE		
Triple Stick Adhesive Tube	29 oz Cartridges	391077	1/8"	355	Top Step, Cap-A-Tread Center, & Riser	Alternative: Urethane-based Construction Adhesive
			3/16"	158		
			1/4"	89		
			5/16"	57		
			3/8"	39		
MSS-20 Gloss Seam Sealer	16 oz	186869	400-600 LF / Kit		Top Step Shim	Alternative: Generic PVC Cement Generic applicator bottle recommended