

| Style | SPACIA XPRESS 2.5MM |
|------------------------------------|--|
| Construction | Luxury Vinyl Tile Non-ortho phthalate |
| Classification | ASTM F1700 Class III, Type B |
| Total Thickness | 2.5 mm |
| Wear Layer Thickness | 20 mil |
| Wear Layer | Quantum Guard Elite® |
| Sizes | 18" x 18" 7.25" x 48" |
| Colors | 5 |
| Packaging | 7.25 x 48 - 18 piece(s), 43.5 Square Feet (4.041), 18 x 18 - 12 piece(s), 27 Square Feet (2.508), 18 x 18 - 18 piece(s), 27 Square Feet (2.508), |
| Adhesive | V-88 Transitional Full Spread Adhesive V-95 Full Spread (2-part Epoxy) XpressStep for LVT & Sheet Vinyl Full Coverage Spray MoistureLoc Full Spread (One Component) |
| Installation Method | All arrows in the same direction. |
| Testing | |
| HUD/FHA | Meets |
| Flexibility (ASTM F137) | Passes- 1" Mandrel - No Crack/Break |
| Dimensional Stability (ASTM F2199) | Passes- Max 0.020 in/lin ft |
| Squareness (ASTM F2055) | Passes- Max 0.010" |
| Static Load (ASTM F970 mod.) | Passes - 2,000 PSI; Residual Indent \leq 0.005" |
| Residual Indentation (ASTM F1914) | Passes- < 8% Avg / 10% Single Value |
| Flooring Radiant Panel (ASTM E648) | Passes- Class 1; \geq 0.45 watts/cm ² |
| Smoke Density (ASTM E662) | Passes- \leq 450 |
| Slip Resistance (ASTMC1028) | Passes- \geq 0.5 Leather; 0.6 Rubber |
| Resistance to Light (ASTM F1515) | Passes |
| Chemical Resistance (ASTM F925) | Passes |
| Resistance to Heat (ASTM F1514) | Passes |
| Environmental Data | |
| Indoor Air Quality | FloorScore Certified; CDPH v1.2-2017 |
| Product Declarations | Third Party Verified EPD Third Party Verified HPD |
| LEED Scoreboard | Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials |
| Manufacturing | Madison, GA (USA) |
| Warranty | |