

## Vivendi Collection

Style	Circ (Modular)	Montage (Modular)	Teres (Modular)
Construction	Tip Sheared Patterned Loop	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Yarn / Solution	Yarn / Solution	Yarn / Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	11 (43.31 per 10 cm)	11 (43.31 per 10 cm)	11 (43.31 per 10 cm)
Density	6,624 (246.13 kg/m <sup>3</sup> )	6,545 (243.20 kg/m <sup>3</sup> )	6,272 (249.37 kg/m <sup>3</sup> )
Pile Thickness	0.125" (3.18 mm)	0.132" (3.35 mm)	0.132" (3.00 mm)
Weight	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )	24 oz/yd <sup>2</sup> (814 g/m <sup>2</sup> )	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )
Backing Type	Infinity <sup>®</sup> 2 Modular	Infinity <sup>®</sup> 2 Modular	Infinity <sup>®</sup> 2 Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	13	13	13
Packaging	8 yd <sup>2</sup> / 18 Tiles	8 yd <sup>2</sup> / 18 Tiles	8 yd <sup>2</sup> / 18 Tiles
Adhesive	Infinity Adhesive	Infinity Adhesive	Infinity Adhesive
Installation Method	Vertical Ashlar	Monolithic	Monolithic

### Testing

Dimensional Stability (Aachen Test)	Passes	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes	Passes
Hexapod (ASTM D5252) TARR	4	3.5	3.5

### Environmental Data

NSF/ANSI 140 Certification	Infinity <sup>®</sup> 2 Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	EPD, HPD
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, <a href="http://mindfulmaterials.origin.build">mindfulmaterials.origin.build</a> , for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered

### Warranty

Limited Lifetime Wear & Backing Warranty  
 Limited 15-Year XGUARD<sup>®</sup> Stain Resistant Warranty  
 Limited 15-Year ColorSafe<sup>®</sup> Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.