

## Wild Threads Collection

Style	Rooted (Modular)	Seedling (Modular)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Type 6 Nylon	Type 6 Nylon
Dye Method	Solution/Yarn	Solution/Yarn
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	11 (43.31 per 10 cm)	11 (43.31 per 10 cm)
Density	7,613 (282.88 kg/m <sup>3</sup> )	7,540 (280.17 kg/m <sup>3</sup> )
Pile Thickness	.096" (2.44 mm)	.092" (2.34 mm)
Weight	20 oz/yd <sup>2</sup> (678 g/m <sup>2</sup> )	19 oz/yd <sup>2</sup> (644 g/m <sup>2</sup> )
Backing Type	Infinity® 2 Modular, rEvolve® II Modular	Infinity® 2 Modular, rEvolve® II Modular
Size	12" x 36" (30.48 X 91.44 cm)	12" x 36" (30.48 X 91.44 cm)
Colors	18	18
Packaging	5.33 yd <sup>2</sup> / 16 Tiles	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	Infinity 2 Adhesive XpressStep Spray FreeLock Tabs (Infinity 2 only)	Infinity 2 Adhesive XpressStep Spray FreeLock Tabs (Infinity 2 only)
Installation Method	Monolithic, Vertical Ashlar	Vertical Ashlar
<b>Testing</b>		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.0	3.0
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, rEvolve® II Modular	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3), visit website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> , for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl verified Silver (Infinity 2 Modular)	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262