

Style	SPACIA ABSTRACT
Construction	Luxury Vinyl Tile Non-ortho phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.098" / 2.5 mm
Wear Layer Thickness	20 mil
Wear Layer	Quantum Guard Elite
Sizes	12" x 18", 12" x 24", 18" x 18", 6" x 36", 7.25" x 48"
Colors	21
Packaging	12" x 18" - 30 piece, 45 Square Feet (4.181), 0.749 Lbs/SF 12" x 18" - 18 piece, 27 Square Feet (2.508), 0.749 Lbs/SF 18" x 18" - 18 piece, 27 Square Feet (2.508), 0.749 Lbs/SF 7.25" x 48" - 12 piece, 27 Square Feet (2.508), 0.749 Lbs/SF 18" x 18" - 30 piece, 45 Square Feet (4.181), 0.749 Lbs/SF 7.25" x 48" - 30 piece, 45 Square Feet (4.181), 0.749 Lbs/SF 12" x 18" - 18 piece, 43.5 Square Feet (4.041), 0.749 Lbs/SF 18" x 18" - 12 piece, 27 Square Feet (2.508), 0.749 Lbs/SF 12" x 18" - 12 piece, 27 Square Feet (2.508), 0.749 Lbs/SF 18" x 18" - 18 piece, 43.5 Square Feet (4.041), 0.749 Lbs/SF - 12 piece, 27 Square Feet (2.508), 0.749 Lbs/SF - 18 piece, 27 Square Feet (2.508), 0.749 Lbs/SF - 30 piece, 45 Square Feet (4.181), 0.749 Lbs/SF
Adhesive	V-88 Full Spread MoistureLoc Full Spread (One Component) V-95 Full Spread (2-part Epoxy) XpressStep for LVT & Sheet Vinyl Full Coverage Spray Available with QuickStix pre-applied adhesive
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.
Testing	
HUD/FHA	Passes
Flexibility (ASTM F137)	Passes- 1" Mandrel - No Crack/Break
Dimensional Stability (ASTM F2199)	Passes- Max 0.020 in/lin ft
Squareness (ASTM F2055)	Passes- Max 0.010"
Static Load (ASTM F970 mod.)	Passes- 2,000 PSI; Residual Indent \leq 0.005"
Residual Indentation (ASTM F1914)	Passes- $<$ 8% Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes- Class 1; \geq 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes- \leq 450
Slip Resistance (ASTMC1028)	Passes- \geq 0.5 Leather; 0.6 Rubber
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes
Environmental Data	
Rapidly Renewable Content	Contains 2% rapidly renewable resource content
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
Product Declarations	Third Party EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3), visit website for more information
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosures & Optimizations - EPDs, Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information
Manufacturing	Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl Verified Silver
Warranty	
Warranty	15 Years