

Specification

FreLock Tabs (3x3) Specification

For Installation of Mannington's Infinity 2 & Infinity 2 MG Modular Backings

CONSTRUCTION

Double-sided tape with fabric carrier

Backing:	Fabric Carrier
Adhesive:	Acrylic Dispersion
Liner:	Polyester, Silicone-coated

SPECIFICATIONS

Size:	3" x 3" (Perforated Tab)
Roll Length:	130 feet
Tabs per Roll:	500
Coverage:	With 24" x 24" modular tile: 150 sq. yds. (Monolithic or Quarter Turn) 100 sq. yds. (All other methods) With 18" x 36" or 12" x 48" modular plank: 110 sq. yds. (Monolithic) 80 sq. yds. (All other methods)
Thickness:	8.6 mil (without any liners), each liner ~3.5 mil
SAP Order Code:	385692 – 1 Roll
Shelf Life:	18 months from manufacture date on unopened containers
Moisture Limits:	Infinity 2 - No moisture testing required with FreLock Tabs using the floating installation method provided the slab meets ASTM F-710 (except where explicitly allowed by our installation instructions) including proof of the presence of an intact moisture vapor barrier per ASTM E-1745 (Class B or Better) no standing water, no free liquids present, no evidence of moisture staining, or hydrostatic pressure and a pH level that does not exceed 12. If these requirements are not met, or when installing with the double stick method the limits are 95% RH / 10 lbs. CC / 12 pH Infinity 2 MG - No moisture testing required with FreLock Tabs using the floating installation method provided the slab has no standing water, no free liquids present, no evidence of moisture staining, or hydrostatic pressure. Infinity 2 MG Cushion & rEvolve II - FreLock Tabs are not approved for use with these backings.

NOTE:

- No Moisture testing option is for floating installations only. Not applicable to Double Stick.
- Mannington's Universal Primer is required with all double stick installation methods.

Specifications are subject to nominal manufacturing variances. Specifications are subject to change without notice when shortages occur or when technological advancements provide improved product performance.