

QuickStix® Field Applied Tape Specification

DESCRIPTION

Mannington Commercial QuickStix tape for Attune, rubber tile and sheet flooring, is a solvent free, poly-acrylic, field-applied system that is recommended for the installation of approved commercial rubber tile and sheet over porous and non-porous substrates. This product is ideal for high moisture and when immediate use and heavy rolling or point load performance is a requirement. The product reduces the need for two-part adhesives.

FEATURES

- Quick installation
- Approved in areas with heavy rolling loads and heavy static loads
- Open to foot traffic immediately after installation
- No occupancy disruption, as associated with traditional liquid adhesives
- Solvent free
- Low VOC
- No use or transport of adhesive pails

APPLICATION

May be used on porous and non-porous surfaces, such as metal, suspended wood, fiberglass and existing properly prepared flooring, and concrete substrates with up to 90% in-situ Relative Humidity as determined per latest version of ASTM F2170. The pH limitations is 10 when using Mannington Premium Universal Primer.

SUBSTRATE PREPARATION

Follow concrete substrate preparation guidelines for resilient flooring as outlined in latest version of ASTM F710. For installation over Mannington Commercial approved panel substrates, follow ASTM F1482. The substrate must be sound, flat, smooth, dry and clean. Do not use on substrates that have been chemically cleaned or abated. Remove any dirt, dust, wax, loose paint, existing adhesives, concrete sealers, curing and parting agents and all other foreign matter that would cause staining or interfere with a proper bond. Use appropriate high-quality Portland-based patching compound designed for this purpose.

The room temperature, as well as flooring materials and adhesive, must be maintained between 65°-85°F, and the relative humidity between 35-55% for 48 hours prior to, during and after the installation.

PRIMER

The use of Mannington Universal Primer is required for the installation of Mannington Commercial QuickStix for Rubber Tile products over porous or non-porous substrates. Warranty will be voided if the primer is not used. All wood substrates and gypcrete substrates require two-coat application.

- One coat of Primer is required for RH levels up to 90% and below.
- Coverage: 350-400 ft² per gallon (one coat)

Specification

TAPE PACKAGING

Rolls - 30" wide x 100' long

TECHNICAL DATA

Proprietary acrylic, highly plasticizer resistant

Thickness: 5 mils (approx. 0.18 mm)

Release paper liner: Siliconized paper

Release paper liner thickness: 0.005" (0.13mm)

WARRANTY

Mannington Commercial QuickStix for Attune, rubber tile and sheet flooring, is backed by a limited Commercial Warranty for bond and manufacturing defects. The Mannington Commercial QuickStix for Attune, rubber tile and sheet flooring, adhesive bond warranty matches the product warranty, which will vary by product type.

SAFETY AND CLEAN UP

- Dried adhesive may require the use of an adhesive remover such as alcohol-based hand sanitizer/wipes.
- Collect and dispose of release paper liner in accordance with local, state and federal requirements.

DISCLAIMER

Users should determine the suitability of this information or product for their own purpose or application. Mannington Commercial is not responsible for the misuse of this product. For full details, please check Mannington Commercial's QuickStix for Attune, rubber tile and sheet flooring, Installation Instructions.