

Studio Loop Collection

Style	Amble (Modular)	Grooveform (Modular)
Construction	Patterned Loop	Patterned Loop
Face Fiber	Type 6.6 Nylon	Type 6.6 Nylon
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	12 (4724 per 10 cm)	12 (4724 per 10 cm)
Density	6,796 (252.53 kg/m ³)	6,796 (252.53 kg/m ³)
Pile Thickness	.114" (2.90 mm)	.114" (2.90 mm)
Weight	22 oz/yd ² (746 g/m ²)	22 oz/yd ² (746 g/m ²)
Backing Type	Infinity® 2 Modular, rEvoIve® II Modular	Infinity® 2 Modular, rEvoIve® II Modular
Size	12" x 36" (30.48 X 91.44 cm)	12" x 36" (30.48 X 91.44 cm)
Colors	15	15
Packaging	5.33 yd ² / 16 Tiles	5.33 yd ² / 16 Tiles
Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs (Infinity 2 and Infinity 2 MG Only)	Infinity 2 Adhesive XpressStep Spray FreLock Tabs (Infinity 2 and Infinity 2 MG Only)
Installation Method	Monolithic, Vertical Ashlar, Horizontal Brick Ashlar	Monolithic, Vertical Ashlar, Horizontal Brick Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATOC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methanamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5
Environmental Data		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, rEvoIve® II Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3), visit website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Low Emitting Materials Green Label Plus certificate	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Verified Silver	
Warranty		
	Limited Lifetime Wear & Backing Warranty 15-Year ColorSafe® Bleach Resistant Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262

Studio Loop Collection

Style	Loopfield (Modular)	Sketchflow (Modular)
Construction	Patterned Loop	Patterned Loop
Face Fiber	Type 6.6 Nylon	Type 6.6 Nylon
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	13 (51.18 per 10 cm)	12 (47.24 per 10 cm)
Density	6,131 (227.82 kg/m ³)	6,655 (247.29 kg/m ³)
Pile Thickness	.098" (2.49 mm)	.117" (2.97 mm)
Weight	17 oz/yd ² (576 g/m ²)	22 oz/yd ² (746 g/m ²)
Backing Type	Infinity® 2 Modular, rEvolve® II Modular	Infinity® 2 Modular, rEvolve® II Modular
Size	12" x 36" (30.48 X 91.44 cm)	12" x 36" (30.48 X 91.44 cm)
Colors	15	15
Packaging	5.33 yd ² / 16 Tiles	5.33 yd ² / 16 Tiles
Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs (Infinity 2 and Infinity 2 MG Only)	Infinity 2 Adhesive XpressStep Spray FreLock Tabs (Infinity 2 and Infinity 2 MG Only)
Installation Method	Monolithic, Vertical Ashlar, Horizontal Brick Ashlar	Monolithic, Vertical Ashlar, Horizontal Brick Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methamphetamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5
Environmental Data		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, rEvolve® II Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1-A3), visit website for more information	
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Low Emitting Materials Green Label Plus certificate	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Verified Silver	
Warranty		
	Limited Lifetime Wear & Backing Warranty 15-Year ColorSafe® Bleach Resistant Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262