

Style	SPACIA STONE
Construction	Luxury Vinyl Tile Non-ortho phthalate
Classification	ASTM F1700 Class III, Type B
Total Thickness	0.098" / 2.5 mm
Wear Layer Thickness	20 mil
Wear Layer	Quantum Guard Elite
Sizes	12" x 18", 12" x 24", 18" x 18", 36" x 36"
Colors	28
Packaging	18''' x 18''' - 12 piece, 27 Square Feet (2.508), 0.749 Lbs/SF 12''' x 18''' - 18 piece, 27 Square Feet (2.508), 0.749 Lbs/SF 18''' x 18''' - 5 piece, 45 Square Feet (4.181), 0.749 Lbs/SF 12''' x 18''' - 12 piece, 27 Square Feet (2.508), 0.749 Lbs/SF 18''' x 18''' - 18 piece, 27 Square Feet (2.508), 0.749 Lbs/SF - 12 piece, 27 Square Feet (2.508), 0.749 Lbs/SF - 18 piece, 27 Square Feet (2.508), 0.749 Lbs/SF
Adhesive	V-88 Full Spread MoistureLoc Full Spread (One Component) V-95 Full Spread (2-part Epoxy) XpressStep for LVT & Sheet Vinyl Full Coverage Spray Available with QuickStix pre-applied adhesive
Installation Method	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.
Testing	
Environmental Data	
Rapidly Renewable Content	Contains 2% rapidly renewable resource content
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
Product Declarations	Third Party EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3), visit website for more information
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosures & Optimizations - EPDs, Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information
Manufacturing	Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl Verified Silver
Warranty	