

Dapper Dialogue Collection

Style	Arie	Deree
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/12 (47.24 per 10 cm)
Stitches Per Inch	12 (47.24 per 10 cm)	11 (43.31 per 10 cm)
Density	6,212 (230.83 kg/m ³)	5,092 (189.21 kg/m ³)
Pile Thickness	0.113" (2.87 mm)	0.111" (2.82 mm)
Weight	20 oz/yd ² (678 g/m ²)	16 oz/yd ² (542 g/m ²)
Backing Type	Infinity [®] 2 Modular - rEvolve II Modular	Infinity [®] 2 Modular - rEvolve II Modular
Size	12" x 36" (30.48 cm X 91.44 cm)	12" x 36" (30.48 cm X 91.44 cm)
Colors	16	8
Adhesive	Infinity [®] 2 Adhesive XpressStep Spray FreLock Tabs - Infinity [®] 2 Modular only	Infinity [®] 2 Adhesive XpressStep Spray FreLock Tabs - Infinity [®] 2 Modular only
Installation Method	Monolithic, Vertical Ashlar	Monolithic, Vertical Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	less than 3.0 KV	less than 3.0 KV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5
Environmental Data		
NSF/ANSI 140 Certification	Infinity 2 Modular - Gold/ rEvolve II Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD 105% Cradle to Gate (A1-A3); see website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD [®] Stain Resistant Warranty Limited 15-Year ColorSafe [®] Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

Dapper Dialogue Collection

Style	Patricia	Rachel
Construction	Textured Patterned Loop	Tip-Sheared Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	1/12 (47.24 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10 cm)	12 (47.24 per 10 cm)
Density	5,257 (195.34 kg/m ³)	6,713 (249.44 kg/m ³)
Pile Thickness	0.113" (2.87 mm)	.096" (2.44 mm)
Weight	16 oz/yd ² (542 g/m ²)	18 oz/yd ² (610 g/m ²)
Backing Type	Infinity [®] 2 Modular - rEvolve II Modular	Infinity [®] 2 Modular - rEvolve II Modular
Size	12" x 36" (30.48 cm X 91.44 cm)	12" x 36" (30.48 cm X 91.44 cm)
Colors	8	16
Adhesive	Infinity [®] 2 Adhesive XpressStep Spray FreLock Tabs - Infinity [®] 2 Modular only	Infinity [®] 2 Adhesive XpressStep Spray FreLock Tabs - Infinity [®] 2 Modular only
Installation Method	Monolithic, Vertical Ashlar	Monolithic, Vertical Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	less than 3.0 KV	less than 3.0 KV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5
Environmental Data		
NSF/ANSI 140 Certification	Infinity 2 Modular - Gold/ rEvolve II Modular - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD 105% Cradle to Gate (A1-A3); see website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered	
Warranty		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD [®] Stain Resistant Warranty Limited 15-Year ColorSafe [®] Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Cut piles, cut and loops and tip-sheared constructions are not recommended for heavy commercial traffic, corridors or through channeled traffic. Please contact your Mannington Commercial representative for information regarding these constructions and your specific end use application.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.