

Specification

Premium Universal Primer Specification

DESCRIPTION

Mannington's Premium Universal Primer (pH Blocker) is a white acrylic latex solution made to neutralize excess alkali that is also recommend as a primer coat to prevent over absorption of adhesive and to ensure a better bond. Formulated with an antimicrobial agent, it provides protection against bacteria, fungi, and mildew in the wet or dry state.

ADVANTAGES

- CRI GLP Certified
- No Solvents
- Low VOC's / Low Odor
- Non-Flammable
- Freeze / Thaw stable

APPLICATION

For use over: Concrete (porous and non-porous) plywood, floor patch, acoustical concrete and other porous surfaces.
Do Not Use: over surfaces such as epoxy, quarry tile, ceramic tile or sheet vinyl.

SURFACE PREPARATION

Substrate must be sound, smooth, clean, level, and dry. It must be free of dust, dirt, wax, paint, incompatible curing compounds or fire-retardant chemicals, release agents, sealers or any other foreign substance that might interfere with a good bond. Vacuum or sweep clean.

INSTRUCTIONS

Shake before use. Pour primer onto substrate. Apply generously using a medium nap paint roller. For large jobs, Mannington Premium Universal Primer may be applied with a garden sprayer, airless rig or regular paint spray equipment. Allow a minimum of 1-hour dry time before installing flooring. When using to neutralize excess alkali, test the pH level. If pH remains above recommended limits, apply a second coat and retest pH level. Up to 1-hour open time depending on the porosity of the subfloor.

NOTE: This product MUST be used with Integra HP carpet, UltraBac RE carpet, and QuickStix products.

ROLLER SIZE & COVERAGE

Over Porous surfaces: Medium nap paint roller / Coverage: 350-400 sq. ft./gal

PACKAGING

Size: 4 Gallons, 1 Gallon
Order Code: 293549, 293552
Weight: 37 lbs., 9.25 lbs

Installation Guidelines

STORAGE

Store Mannington's Premium Universal Primer in climate controlled interior locations only between 50 - 90°F. Protect from freezing. Mannington's Premium Universal Primer is freeze/thaw stable to 10°F, but prolonged or repeated freeze/thaw cycles should be avoided.

Should the Mannington's Premium Universal Primer freeze, allow to thaw at room temperature and stir well before using. Mannington's Premium Universal Primer has a two-year shelf life on unopened containers.

CLEAN UP

Wet primer should be immediately removed from tools or surfaces with a clean, soapy, damp cloth. Dried primer can be removed with denatured alcohol, mineral spirits, or adhesive solvent.

WARRANTY

Mannington's Premium Universal Primer is manufactured according to exacting quality control standards specifically for the installation of Mannington's floor coverings. Mannington's Premium Universal Primer is warranted to be free from manufacturing defects for two years.