

Style	Relay Modular (Non-Ortho Phthalate)	Transmit Modular (Non-Ortho Phthalate)
Construction	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Antron® Lumena™ Type 6,6 Nylon	Antron® Lumena™ Type 6,6 Nylon
Dye Method	Solution	Solution
Gauge	5/64 (50.39 per 10 cm)	5/64 (50.39 per 10 cm)
Stitches Per Inch	10 (39.37 per 10 cm)	10 (39.37 per 10 cm)
Density	6,690 (248.95 kg/m <sup>3</sup> )	6,690 (248.95 kg/m <sup>3</sup> )
Pile Thickness	0.113" (2.90 mm)	0.113" (2.90 mm)
Weight	21 oz/yd <sup>2</sup> (712 g/m <sup>2</sup> )	21 oz/yd <sup>2</sup> (712 g/m <sup>2</sup> )
Backing Type	Infinity® Modular	Infinity® Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	8	8
Packaging	6.22 yd <sup>2</sup> / 14 Tiles	6.22 yd <sup>2</sup> / 14 Tiles
Adhesive	Infinity® Adhesive	Infinity® Adhesive
Installation Method	Horizontal Brick Ashlar, Vertical Ashlar, Monolithic	Horizontal Brick Ashlar, Vertical Ashlar, Monolithic

**Testing**

Dimensional Stability (AACHEN Test)	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR Rating	3.5

**Environmental Data**

NSF/ANSI-140 Certification	Infinity® Modular - Gold
Recycled Content	Contains pre-consumer recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Recyclability	LOOP®
Product Declarations	EPD, HPD
LEED Scoreboard	May contribute to LEED credits: LEED 2009: MRc5 Regional Materials; MRc6 Rapidly Renewable Materials; IEQ4.1 Low Emitting Adhesives; IEQ4.3 Low Emitting Materials - Flooring LEED v4: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mM Origin website, <a href="http://mindfulmaterials.origin.build">mindfulmaterials.origin.build</a> , for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered

**Warranty**

Limited Lifetime Wear & Backing Warranty  
 Limited 15 Year XGUARD® Stain Resistant Warranty  
 Limited 15 Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent, pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.

**Crafted with purpose**

For more information, contact your local Mannington representative or visit [manningtoncommercial.com](http://manningtoncommercial.com)