

## Studio Loop Collection

Style	Amble (Modular)	Grooveform (Modular)
Construction	Patterned Loop	Patterned Loop
Face Fiber	Type 6.6 Nylon	Type 6.6 Nylon
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	12 (47.24 per 10 cm)	12 (47.24 per 10 cm)
Density	6,796 (252.53 kg/m <sup>3</sup> )	6,796 (252.53 kg/m <sup>3</sup> )
Pile Thickness	.114" (2.90 mm)	.114" (2.90 mm)
Weight	22 oz/yd <sup>2</sup> (746 g/m <sup>2</sup> )	22 oz/yd <sup>2</sup> (746 g/m <sup>2</sup> )
Backing Type	Infinity <sup>®</sup> 2 Modular, rEvolve <sup>®</sup> II Modular	Infinity <sup>®</sup> 2 Modular, rEvolve <sup>®</sup> II Modular
Size	12" x 36" (30.48 X 91.44 cm)	12" x 36" (30.48 X 91.44 cm)
Colors	15	15
Packaging	5.33 yd <sup>2</sup> / 16 Tiles	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs (Infinity 2 and Infinity 2 MG Only)	Infinity 2 Adhesive XpressStep Spray FreLock Tabs (Infinity 2 and Infinity 2 MG Only)
Installation Method	Monolithic, Vertical Ashlar, Horizontal Brick Ashlar	Monolithic, Vertical Ashlar, Horizontal Brick Ashlar

### Testing

Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; $\geq 0.45$ watts/cm <sup>2</sup>	Passes - Class 1; $\geq 0.45$ watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - $\leq 450$	Passes - $\leq 450$
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5

### Environmental Data

NSF/ANSI 140 Certification	Infinity <sup>®</sup> 2 Modular - Gold, rEvolve <sup>®</sup> II Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	Third Party verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3), visit website for more information
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Low Emitting Materials Green Label Plus certificate
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Verified Silver

### Warranty

Limited Lifetime Wear & Backing Warranty 15-Year ColorSafe<sup>®</sup> Bleach Resistant  
 Limited 15-Year XGUARD<sup>®</sup> Stain Resistant Warranty  
 Limited 15-Year ColorSafe<sup>®</sup> Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262

## Studio Loop Collection

Style	Loopfield (Modular)	Sketchflow (Modular)
Construction	Patterned Loop	Patterned Loop
Face Fiber	Type 6.6 Nylon	Type 6.6 Nylon
Dye Method	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	13 (51.18 per 10 cm)	12 (47.24 per 10 cm)
Density	6,131 (227.82 kg/m <sup>3</sup> )	6,655 (247.29 kg/m <sup>3</sup> )
Pile Thickness	.098" (2.49 mm)	.117" (2.97 mm)
Weight	17 oz/yd <sup>2</sup> (576 g/m <sup>2</sup> )	22 oz/yd <sup>2</sup> (746 g/m <sup>2</sup> )
Backing Type	Infinity® 2 Modular, rEvolve® II Modular	Infinity® 2 Modular, rEvolve® II Modular
Size	12" x 36" (30.48 X 91.44 cm)	12" x 36" (30.48 X 91.44 cm)
Colors	15	15
Packaging	5.33 yd <sup>2</sup> / 16 Tiles	5.33 yd <sup>2</sup> / 16 Tiles
Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs (Infinity 2 and Infinity 2 MG Only)	Infinity 2 Adhesive XpressStep Spray FreLock Tabs (Infinity 2 and Infinity 2 MG Only)
Installation Method	Monolithic, Vertical Ashlar, Horizontal Brick Ashlar	Monolithic, Vertical Ashlar, Horizontal Brick Ashlar

### Testing

Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Smoke Density (ASTM E662)	Passes - ≤ 450	Passes - ≤ 450
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5

### Environmental Data

NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, rEvolve® II Modular - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	Third Party verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1-A3), visit website for more information
LEED	Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients (HPDs); IEQc2 - Low Emitting Materials Green Label Plus certificate
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Verified Silver

### Warranty

Limited Lifetime Wear & Backing Warranty 15-Year ColorSafe® Bleach Resistant  
 Limited 15-Year XGUARD® Stain Resistant Warranty  
 Limited 15-Year ColorSafe® Bleach Resistant Warranty

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262