

Style	SPACIA WOOD
<b>Construction</b>	Luxury Vinyl Tile Non-ortho phthalate
<b>Classification</b>	ASTM F1700 Class III, Type B
<b>Total Thickness</b>	0.098" / 2.5 mm
<b>Wear Layer Thickness</b>	20 mil
<b>Wear Layer</b>	Quantum Guard Elite
<b>Edge Treatment</b>	Microbevel
<b>Sizes</b>	6" x 36", 7.25" x 48"
<b>Colors</b>	68
<b>Packaging</b>	7.25" x 48" - 18 piece, 43.5 Square Feet (4.041), 0.749 Lbs/SF 6" x 36" - 30 piece, 45 Square Feet (4.181), 0.749 Lbs/SF 7.25" x 48" - 9 piece, 21.75 Square Feet (2.021), 0.749 Lbs/SF 7.25" x 48" - 30 piece, 43.5 Square Feet (4.041), 0.749 Lbs/SF 6" x 36" - 9 piece, 45 Square Feet (4.181), 0.749 Lbs/SF 7.25" x 48" - 18 piece, 21.75 Square Feet (2.021), 0.749 Lbs/SF 7.25" x 48" - 9 piece, 43.5 Square Feet (4.041), 0.749 Lbs/SF 7.25" x 48" - 30 piece, 21.75 Square Feet (2.021), 0.749 Lbs/SF 6" x 36" - 18 piece, 45 Square Feet (4.181), 0.749 Lbs/SF 7.25" x 48" - , 43.5 Square Feet (4.041), 0.749 Lbs/SF
<b>Adhesive</b>	V-88 Full Spread MoistureLoc Full Spread (One Component) V-95 Full Spread (2-part Epoxy) XpressStep for LVT & Sheet Vinyl Full Coverage Spray Available with QuickStix pre-applied adhesive
<b>Installation Method</b>	All arrows in the same direction. Planks should have end joints offset by at least 6" and staggered to create a random appearance. Tiles should be installed block or staggered; when quarter turned, arrows should alternate.
<b>Testing</b>	
<b>HUD/FHA</b>	Passes
<b>Flexibility (ASTM F137)</b>	Passes- 1" Mandrel - No Crack/Break
<b>Dimensional Stability (ASTM F2199)</b>	Passes- Max 0.020 in/lin ft
<b>Squareness (ASTM F2055)</b>	Passes- Max 0.010"
<b>Static Load (ASTM F970 mod.)</b>	Passes- 2,000 PSI; Residual Indent ≤ 0.005"
<b>Residual Indentation (ASTM F1914)</b>	Passes- < 8% Avg / 10% Single Value
<b>Flooring Radiant Panel (ASTM E648)</b>	Passes- Class 1; ≥ 0.45 watts/cm <sup>2</sup>
<b>Smoke Density (ASTM E662)</b>	Passes- ≤ 450
<b>Slip Resistance (ASTMC1028)</b>	Passes- ≥ 0.5 Leather; 0.6 Rubber
<b>Resistance to Light (ASTM F1515)</b>	Passes
<b>Chemical Resistance (ASTM F925)</b>	Passes
<b>Resistance to Heat (ASTM F1514)</b>	Passes
<b>Environmental Data</b>	
<b>Rapidly Renewable Content</b>	Contains 2% rapidly renewable resource content
<b>Indoor Air Quality</b>	FloorScore Certified; CDPH v1.2-2017
<b>Carbon Offset</b>	105% Cradle to Gate (A1-A3), visit website for more information
<b>LEED Scoreboard</b>	May contribute to LEED credits: Building Product Disclosures & Optimizations - EPDs, Building Product Disclosure & Optimization - Sourcing Raw Materials; IEQc2 - Low Emitting Materials
<b>mindful MATERIALS</b>	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information
<b>Manufacturing</b>	Madison, GA (USA) - ISO 14001 EMS & ISO 9001 QMS Registered, +Vantage Vinyl Verified Silver
<b>Warranty</b>	
<b>Warranty</b>	Limited 15-Year Commercial Warranty, Limited 15-Year Quantum Guard Elite® Wear Warranty