



**Tufted Traditions Collection**

<b>Style</b>	<b>Carthage Legacy (Modular)</b>	<b>Gametime III (Modular)</b>
<b>Construction</b>	Non-Patterned Loop	Non-Patterned Loop
<b>Face Fiber</b>	Type 6,6 Nylon	Type 6,6 Nylon
<b>Dye Method</b>	Solution/Yarn	Solution/Yarn
<b>Gauge</b>	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
<b>Stitches Per Inch</b>	10 (39.37 per 10 cm)	6.33 (24.92 per 10 cm)
<b>Density</b>	7,500 (278.68 kg/m <sup>3</sup> )	8,372 (311.09 kg/m <sup>3</sup> )
<b>Pile Thickness</b>	0.096" (2.44 mm)	0.086" (2.18 mm)
<b>Weight</b>	20 oz/yd <sup>2</sup> (678 g/m <sup>2</sup> )	20 oz/yd <sup>2</sup> (678 g/m <sup>2</sup> )
<b>Backing Type</b>	Infinity® 2 Modular	Infinity® 2 Modular
<b>Size</b>	24" x 24" (60.96 cm x 60.96 cm)	24" x 24" (60.96 cm x 60.96 cm)
<b>Colors</b>	6	6
<b>Packaging</b>	7.1 yd <sup>2</sup> / 16 Tiles	7.1 yd <sup>2</sup> / 16 Tiles
<b>Adhesive</b>	Infinity® 2 Adhesive	Infinity® 2 Adhesive
	XpressStep Spray	XpressStep Spray
<b>Installation Method</b>	Monolithic	Monolithic
<b>Testing</b>		
<b>Dimensional Stability (Aachen Test)</b>	Passes	
<b>Electrostatic Propensity (AATCC 134)</b>	Less than 3.0 kV	
<b>Flooring Radiant Panel (ASTM E648)</b>	Passes - Class 1 ≥ 0.45 watts/cm <sup>2</sup>	
<b>Smoke Density (ASTM E662)</b>	Passes ≤ 450	
<b>Methenamine Pill Test (ASTM D2859)</b>	Passes	
<b>Hexapod (ASTM D5252) TARR</b>	3.0 - heavy	4.0 - severe
<b>Environmental Data</b>		
<b>NSF/ANSI 140 Certification</b>	Infinity® 2 Modular - Gold, UltraBac® RE - Gold, Integra® HP - Gold	
<b>Recycled Content</b>	Contains recycled content	
<b>Indoor Air Quality</b>	CRI Green Label Plus Certified	
<b>Product Declarations</b>	Third Party Verified EPD, HPD	
<b>Carbon Offset</b>	105% Cradle to Gate (A1 - A3), visit website for more information	
<b>LEED</b>	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials	
<b>mindful MATERIALS</b>	Visit mindfulmaterials.com for current transparency information	
<b>Manufacturing</b>	Calhoun, GA (USA) - ISO 14001 Certified, +Vantage Vinyl Verified Silver	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Warranty	
	Limited 15-Year XGUARD® Stain Resistant Warranty	
	Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.



## Tufted Traditions Collection

Style	Carthge Legacy (Broadloom)	Gametime III (Broadloom)
Construction	Non-Patterned Loop	Non-Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution/Yarn	Solution/Yarn
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	10 (39.37 per 10 cm)	6.33 (24.92 per 10 cm)
Density	7,500 (278.88 kg/m <sup>3</sup> )	8,372 (311.09 kg/m <sup>3</sup> )
Pile Thickness	0.096" (2.44 mm)	0.086" (2.18 mm)
Weight	20 oz/yd <sup>2</sup> (678 g/m <sup>2</sup> )	20 oz/yd <sup>2</sup> (678 g/m <sup>2</sup> )
Backing Type	UltraBac® RE	Integra® HP, UltraBac® RE
Size	12' width (3.66 m)	12' width (381 cm)
Colors	6	6
Adhesive	UltraBac® RE	Integra® HP - Integra 2 Adhesive UltraBac® RE - Ultra Adhesive N/A
<b>Testing</b>		
Dimensional Stability (Aachen Test)	Passes	
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1 ≥ 0.45 watts/cm <sup>2</sup>	
Smoke Density (ASTM E662)	Passes ≤ 450	
Methenamine Pill Test (ASTM D2859)	Passes	
Hexapod (ASTM D5252) TARR	3.5 - severe	3.0 - heavy
<b>Environmental Data</b>		
NSF/ANSI 140 Certification	Infinity® 2 Modular - Gold, UltraBac® RE - Gold, Integra® HP - Gold	
Recycled Content	Contains recycled content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 -Low Emitting Materials	
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information	
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl Silver	
<b>Warranty</b>		
	Limited Lifetime Wear & Backing Warranty Limited 15-Year XGUARD® Stain Resistant Warranty Limited 15-Year ColorSafe® Bleach Resistant Warranty	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262 ext. 6913.