

Open Range™

Style	Open Range™
Construction	Thermoset Rubber Plank
Finish	Matte
Classification	ASTM F1344 Type 1 (A), Grade 1
Total Thickness	1/8" (3.2 mm)
Profile	Marbled
Size	6.25" x 42" (165.10 x 1066.80 mm)
Colors	12
Packaging	20 pc, 36.5 ft ² (3.39 m ²), 40 lbs (18.15 kg)
Adhesive	Mannington MR-721 Full Spread, 2-part Epoxy Mannington MR-725 Full Spread 2-part Urethane Mannington MR-911 Full Spread, Single Component Acrylic
QuickStix®	Available with QuickStix® pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in extreme moisture areas.
	Note: Must use MR-721, MR-725, or Quickstix adhesive under hospital beds, heavy rolling load areas, areas subject to dragging force, areas with direct sunlight, or where topical moisture would be a concern.
Testing	
HUD/FHA	Meets/Exceeds
ADAG (American Disability Act Guidelines)	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.15%
Squareness (ASTM F2055)	Passes - Max 0.010"
Hardness (ASTM D2240)	Passes - Shore Type A ≥ 85
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 800 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Acoustic IIC (ASTM E492)	50 - 6" Concrete with Drop Ceiling
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change
Environmental Data	
Recycled Content	Contains 4% rapidly renewable resource content by total product weight.
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
Product Declarations	EPD, HPD, Declare Red List Free
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information
Manufacturing	Calhoun, GA (USA)
Warranty	
	Limited 10-Year Commercial Warranty Limited 10-Year Wear Warranty

Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit manningtoncommercial.com