



TX:Style Collection

Style	A La Mode (Modular)	Bark II (Modular)
Construction	Patterned Loop	Tip-Sheared Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Yarn/Solution	Yarn/Solution
Gauge	5/64	5/64
Stitches Per Inch	10.66 (41.97 per 10cm)	11.5 (45.28 per 10cm)
Density	5,781 (214.81 kg/m ²)	6,646 (246.95 kg/m ²)
Pile Thickness	0.137" (3.48 mm)	0.130" (3.30 mm)
Weight	22 oz/yd ² (746 g/m ²)	24 oz/yd ² (814 g/m ²)
Backing Type	Infinity [®] 2 Modular rEvolve II Modular	Infinity [®] 2 Modular rEvolve II Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	16	16
Packaging	8 yd ² / 18 Tiles	8 yd ² / 18 Tiles
Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs -Infinity 2 Modular only	Infinity 2 Adhesive XpressStep Spray FreLock Tabs - Infinity 2 Modular only
Installation Method	Vertical Ashlar	Horizontal Brick Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 KV	Less than 3.0 KV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm ² , Passes (Class 1)	≥ 0.45 watts/cm ² , Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5
Environmental Data		
NSF/ANSI 140 Certification	Infinity [®] 2 Modular - Gold / rEvolve II Modular -Gold	
Recycled Content	Contains Recycled Content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
LEED	May contribute to LEED Credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information.	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
Warranty		
	Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.

TX:Style Collection

Style	Canopy II (Modular)	Squareberry II (Modular)
Construction	Patterned Loop	Tip-Sheared Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Yarn/Solution	Yarn/Solution
Gauge	5/64	5/64
Stitches Per Inch	12.33 (48.54 per 10cm)	12 (47.24 per 10cm)
Density	6,71 (249.37 kg/m ³)	6,133 (227.89 kg/m ³)
Pile Thickness	0.118" (3.00 mm)	0.135" (3.43 mm)
Weight	22 oz/yd ² (746 g/m ²)	23 oz/yd ² (780 g/m ²)
Backing Type	Infinity [®] 2 Modular rEvolve II Modular	Infinity [®] 2 Modular rEvolve II Modular
Size	24" x 24" (60.96 x 60.96 cm)	24" x 24" (60.96 x 60.96 cm)
Colors	16	16
Packaging	8 yd ² / 18 Tiles	8 yd ² / 18 Tiles
Adhesive	Infinity 2 Adhesive XpressStep Spray FreLock Tabs-Infinity 2 modular only	Infinity 2 Adhesive XpressStep Spray FreLock Tabs-Infinity 2 modular only
Installation Method	Horizontal Brick Ashlar	Horizontal Brick Ashlar
Testing		
Dimensional Stability (Aachen Test)	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 KV	Less than 3.0 KV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	4
Environmental Data		
NSF/ANSI 140 Certification	Infinity [®] 2 Modular - Gold / rEvolve II Modular -Gold	
Recycled Content	Contains Recycled Content	
Indoor Air Quality	CRI Green Label Plus Certified	
Product Declarations	Third Party Verified EPD, HPD	
LEED	May contribute to LEED Credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2- Low Emitting Materials	
mindful MATERIALS	Visit mindfulmaterials.com for current transparency information.	
Manufacturing	Calhoun, Georgia (USA) - ISO 14001 Certified	
Warranty		
	Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant	

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.



TX:Style Collection

Style	Bark II (Broadloom)	Canopy II (Broadloom)	Squareberry II (Broadloom)
Construction	Tip-Sheared Patterned Loop	Patterned Loop	Tip-Sheared Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Yarn/Solution	Yarn/Solution	Yarn/Solution
Gauge	5/64	5/64	5/64
Stitches Per Inch	11.5 (45.28 per 10cm)	12.33 (48.54 per 10cm)	12 (47.24 per 10cm)
Density	6,646 (246.95 kg/m ²)	6,711 (249.37 kg/m ²)	6,133 (227.89 kg/m ²)
Pile Thickness	0.130" (3.30 mm)	0.118" (3.00 mm)	0.135" (3.43 mm)
Weight	24 oz/yd ² (814 g/m ²)	22 oz/yd ² (746 g/m ²)	23 oz/yd ² (780 g/m ²)
Backing Type	UltraBac® RE, Integra® HP	UltraBac® RE, Integra® HP	UltraBac® RE, Integra® HP
Size	12' 6" Width	12' 6" Width	12' 6" Width
Colors	16	16	16
Pattern Repeat	18 3/4" W x 21 1/4" L	18 3/4" W x 42 1/4" L	18 3/4" W x 19 1/2" L
Adhesive	Ultra Adhesive Integra-2 Adhesive	Ultra Adhesive Integra-2 Adhesive	Ultra Adhesive Integra-2 Adhesive
Testing			
Dimensional Stability (Aachen Test)	Passes	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 KV	Less than 3.0 KV	Less than 3.0 KV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm ² , Passes (Class 1)	≥ 0.45 watts/cm ² , Passes (Class 1)	≥ 0.45 watts/cm ² , Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes	Passes
Hexapod (ASTM D5252) TARR	3.5	3.5	3.5
Environmental Data			
NSF/ANSI 140 Certification	UltraBac® RE - Gold Integra® HP - Gold		
Recycled Content	Contains Recycled Content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	Third Party Verified EPD, HPD		
LEED	May contribute to LEED Credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
mindful MATERIALS Manufacturing	Visit mindfulmaterials.com for current transparency information. Calhoun, Georgia (USA) - ISO 14001 Certified		
Warranty			
	Limited Lifetime Wear & Backing Limited 15-Year Xguard Stain Resistant Limited 15-Year ColorSafe Bleach Resistant		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to manningtoncommercial.com or call 800.241.2262 ext. 6913.