

Edge Effects® Collection

Style	Cetera®*, Flair*, Lunar, Simplicity*	Cache®*, Etched, Iconic®*, Illusion, Marquee®*, Regal*, Simple, Sophisticate®*
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	5/16" (7.94 mm)	3/8" (9.52 mm)
Profile	Smooth	Smooth
Profile Height	Flair, Simplicity - 3" Cetera®, Lunar, Simplicity - 4" or 4 1/2" Simplicity - 6"	Cache® - 3" Illusion® - 3 1/4" Etched, Simple - 4" Cache®, Iconic®, Marquee®, Sophisticate® - 4 1/4" Regal - 5 1/4"
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	For current transparency information visit mindfulmaterials.com	
Manufacturing	USA	
Warranty		
	Limited 5-Year Commercial Warranty	

Edge Effects® Collection

Style	Double Etched*, Effectual® Chair Rail, Etched*, Simple	Elegance
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/4" (6.35 mm)	3/16" (4.76 mm)
Profile	Smooth	Smooth
Profile Height	Double Etched, Etched, Simple - 4" or 4 1/4" Effectual® Chair Rail - 4" Etched - 6"	6"
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017	
Product Declarations	HPD	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	For current transparency information visit mindfulmaterials.com	
Manufacturing	USA	
Warranty		
Limited 5-Year Commercial Warranty		

Edge Effects® Collection

Style	Quarter Round	*Pre-mitered Inside and Outside corners also available
Construction	Co-extruded Thermoplastic Rubber, Type TP	Co-extruded Thermoplastic Rubber, Type TP
Classification	ASTM F1861 Type TP, Group 1	ASTM F1861 Type TP, Group 1
Finish	Matte	Matte
Total Thickness	1/2" (12.7 mm)	3/16" (4.76 mm)
Profile	Smooth	Smooth
Colors	40 (36 are Accord)	40 (36 are Accord)
Packaging	See Packaging Chart, p.4	See Packaging Chart, p.4
Adhesive	MR101 Acrylic	MR101 Acrylic
Testing		
HUD/FHA	Meets / Exceeds	
ADAG (American Disability Act Guidelines)	Passes	
Flexibility (ASTM F137)	Passes - 1/4" Mandrel - No Crack/Break	
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²	
Smoke Density (ASTM E662)	Passes - < 450	
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change	
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change	
Resistance to Mold/Mildew (ASTM G21/E2180)	Passes - No More Than Slight Change	
Environmental Data		
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017	
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials	
mindful MATERIALS	For current transparency information visit mindfulmaterials.com	
Manufacturing	USA	
Warranty		
	Limited 5-Year Commercial Warranty	