

Style	GASKELL
Construction	Tip Sheared Loop
Face Fiber	Type 6,6
Dye Method	Yarn/Solution
Gauge	0.078125 (50.39)
Stitches Per Inch	11.33 " (44.61 cm)
Density	7016 (260.7 kg/m3)
Pile Thickness	0.118 " (3 mm)
Weight	23 oz/yd2 (780 g/m2)
Size	12' 6"
Colors	12
Packaging	/
Adhesive	Integra® HP - Integra 2 Adhesive UltraBac® RE - Ultra Adhesive
Installation Method	18 3/4" W X 21" L
Testing	
Dimensional Stability (Aachen Test)	N/A
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV
Flooring Radiant Panel (ASTM E648)	≥ 0.45 watts/cm2, Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes
Hexapod (ASTM D5252) TARR	SA & HP - 3.5
Environmental Data	
NSF/ANSI 140 Certification	UltraBac® RE - Gold, Integra® HP - Gold
Recycled Content	Contains recycled content
Indoor Air Quality	CRI Green Label Plus Certified
Product Declarations	Third Party Verified EPD, HPD
Carbon Offset	105% Cradle to Gate (A1 - A3)
LEED	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials
mindful MATERIALS	Visit mindfulmaterials.com , for current transparency information
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl verified Silver (Infinity 2 Modular)
Warranty	
Warranty	Lifetime