

Style	Reset®
Construction	Recycled Rubber Sports Flooring
Classification	ASTM F3041 Class A, Type II (Tile); Class B, Type I (Sheet)
Total Thickness	3/8" (9.0 mm) (Nominal)
Sizes	18" x 18" (457 x 457 mm) Square Edge 24" x 24" (610 x 610 mm) Interlocking 4' x 50' (1.2 x 15 m) Sheet
Colors	9
Packaging	18" x 18" - 1 pc, 2.25 ft <sup>2</sup> (0.209 m <sup>2</sup> ), 4.365 lbs (1.98 kg) 24" x 24" - 1 pc, 4 ft <sup>2</sup> (0.3716 m <sup>2</sup> ), 8 lbs (3.629 kg) 4' x 50' Sheet - 200 ft <sup>2</sup> (18.58 m <sup>2</sup> ) Roll, 412 lbs (186.9 kg) Roll
Adhesive	<b>MR-710</b> Full Spread, Single Component Urethane <b>MR-725</b> Full Spread, 2-part Urethane Available with QuickStix® (Except Reset Sheet) pre-applied adhesive, reducing time and labor required to install the flooring. QuickStix® floors can be used immediately after installation, even in moisture areas. <b>Note:</b> Must use MR-710 or QuickStix adhesive under hospital beds, heavy rolling load areas, areas subject to dragging force, areas with direct sunlight or where topical moisture would be a concern.
<b>Testing</b>	
HUD/FHA	Meets or Exceeds
ADAG (American Disability Act Guidelines)	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.40%
Squareness (ASTM F2055)	Passes - Max 0.030" (Tile)
Static Load (ASTM F970)	Passes - Residual Indent ≤ 0.005"
Static Load (ASTM F970 mod.)	Passes - 400 PSI; Residual Indent ≤ 0.005"
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm <sup>2</sup>
Slip Resistance (ASTM C1028, Dry)	Passes - ≥ 0.5 Leather; 0.6 Rubber
Chemical Resistance (ASTM F925)	Passes - No More Than Slight Change
Resistance to Heat (ASTM F1514)	Passes - < 8 Delta E Color Change
Abrasion Resistance (ASTM D3389)	Passes - < 1g, 1000 Cycles
<b>Environmental Data</b>	
Recycled Content	Black Tones contains a minimum of 91% post-consumer recycled content (Class A) by total product weight. All other colors in Reset contain a minimum of 4% pre-consumer and a minimum of 72% post-consumer recycled Content (Class B) by total product weight.
Indoor Air Quality	FloorScore Certified; CDPH v1.2-2017
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - IEQc2 - Low Emitting Materials Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information
Manufacturing	Made in the USA
<b>Warranty</b>	

Limited 5 Year Commercial Warranty

## Crafted with Purpose

For more information, contact your local Mannington Commercial representative or visit [manningtoncommercial.com](http://manningtoncommercial.com)