

## Spin Remix Collection

Style	Channel RMX (Modular)	Disc RMX (Modular)	RPM RMX (Modular)
Construction	Tip-Sheared Patterned Loop	Textured Patterned Loop	Textured Patterned Loop
Face Fiber	Type 6,6 Nylon	Type 6,6 Nylon	Type 6,6 Nylon
Dye Method	Solution	Solution	Solution
Gauge	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)	1/10 (39.37 per 10 cm)
Stitches Per Inch	12 (4724 per 10 cm)	12 (4724 per 10 cm)	12 (4724 per 10 cm)
Density	6,702 (249.03 kg/m <sup>3</sup> )	7,290 (270.88 kg/m <sup>3</sup> )	6,355 (236.14 kg/m <sup>3</sup> )
Pile Thickness	.123" (3.12 mm)	.120" (3.05 mm)	.115" (2.92 mm)
Weight	23 oz/yd <sup>2</sup> (780 g/m <sup>2</sup> )	24 oz/yd <sup>2</sup> (814 g/m <sup>2</sup> )	20 oz/yd <sup>2</sup> (678 g/m <sup>2</sup> )
Backing Type	Infinity <sup>®</sup> 2 Modular, rEvolve <sup>®</sup> II (PVC-Free) Modular	Infinity <sup>®</sup> 2 Modular, rEvolve <sup>®</sup> II (PVC-Free) Modular	Infinity <sup>®</sup> 2 Modular, rEvolve <sup>®</sup> II (PVC-Free) Modular
Sizes	12" x 36" (30.48 X 91.44 cm)	12" x 36" (30.48 X 91.44 cm)	12" x 36" (30.48 x 91.44 cm)
Colors	10	10	10
Packaging	5.328 yd <sup>2</sup> / 16 Tiles	5.328 yd <sup>2</sup> / 16 Tiles	5.328 yd <sup>2</sup> / 16 Tiles
Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive	Infinity 2 Adhesive
Installation Method	Vertical Ashlar	Vertical Ashlar	Vertical Ashlar
<b>Testing</b>			
Dimensional Stability (Aachen Test)	Passes	Passes	Passes
Electrostatic Propensity (AATCC 134)	Less than 3.0 kV	Less than 3.0 kV	Less than 3.0 kV
Radiant Panel (ASTM E648)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)	≥ 0.45 watts/cm <sup>2</sup> , Passes (Class 1)
Smoke Density (ASTM E662)	≤ 450-Passes	≤ 450-Passes	≤ 450-Passes
Methenamine Pill Test (ASTM D2859)	Passes	Passes	Passes
Hexapod (ASTM D5252) TARR Rating	3.0	3.0	3.0
<b>Environmental Data</b>			
NSF/ANSI 140 Certification	Infinity 2 Modular - Gold / rEvolve II Modular - Gold		
Recycled Content	Contains Recycled Content		
Indoor Air Quality	CRI Green Label Plus Certified		
Product Declarations	Third Party Verified EPD, HPD		
Carbon Offset	105% Cradle to Gate (A1 - A3), visit website for more information		
LEED Scoreboard	May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs; Building Product Disclosure & Optimization - Sourcing Raw Materials; Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials		
mindful MATERIALS	Visit <a href="http://mindfulmaterials.com">mindfulmaterials.com</a> for current transparency information.		
Manufacturing	Calhoun, GA (USA) - ISO 14001 Registered, +Vantage Vinyl™ Verified Silver		
<b>Warranty</b>			
	Limited Lifetime Wear & Backing		
	Limited 15-Year XGUARD <sup>®</sup> Stain Resistant		
	Limited 15-Year ColorSafe <sup>®</sup> Bleach Resistant		

- Specifications are based on averages from normal manufacturing tolerances. Such variations do not affect product performance.
- Protective chair pads are recommended under office chairs with roller casters to preserve appearance and avoid premature wear.
- As with all quality carpets, slight variation in color may occur from dye lot to dye lot.
- Backing or other materials may be changed without prior notice when shortages occur or when technological advancements provide improved product performance.
- This product is intended solely for use as an indoor floor covering and is not recommended or sold for any other purpose.
- The inherent characteristics of geometric linear patterns can result in double-dark or double-light lines at the seam and to some extent pattern run-off or bias. This is not a manufacturing defect, and as such, should be considered when selecting a modular carpet installation method.
- Please make your final selection from an actual swatch. To order samples, go to [manningtoncommercial.com](http://manningtoncommercial.com) or call 800.241.2262