

Cresta Collection

Style	Cresta
Construction	Solid Polymer Core Non-ortho Phthalate
Classification	ASTM F3261 Class I, Type B, Grade 2, Backing Class B
Overall Thickness	0.177" (4.5 mm) includes 0.039" (1 mm) attached underlayment
Wear Layer Thickness	12 Mil (0.3 mm)
Wear Layer	Urethane
Edge Treatment	Micro-beveled
Sizes	7" x 48" (177.8 mm x 1219 mm)
Colors	10
Packaging	7" x 48" - 11 pcs, 25.426 ft ² (2.41 m ²), 35 lbs (15.88 kg)
Installation Method	Floating
Testing	
HUD/FHA	Passes
Dimensional Stability (ASTM F2199)	Passes - Max 0.020 in/lin ft
Squareness (ASTM F2055)	Passes - Max 0.010"
Static Load (ASTM F970 mod.)	Passes- 750 PSI; Residual Indent ≤ 0.003"
Residual Indentation (ASTM F1914)	Passes - < 8% Avg / 10% Single Value
Flooring Radiant Panel (ASTM E648)	Passes - Class 1; ≥ 0.45 watts/cm ²
Smoke Density (ASTM E662)	Passes - ≤ 450
Slip Resistance (ASTM C1028)	Passes - ≥ 0.5 Leather
Resistance to Light (ASTM F1515)	Passes
Chemical Resistance (ASTM F925)	Passes
Resistance to Heat (ASTM F1514)	Passes
Acoustic IIC (ASTM E492)	66 - 6" Slab with Drop Ceiling
Acoustic STC (ASTM E90)	60 - 6" Slab with Drop Ceiling
Environmental Data	
Indoor Air Quality LEED	
mindful MATERIALS	FloorScore Certified; CDPH v1.2-2017 May contribute to LEED credits: Building Product Disclosure & Optimization - EPDs Building Product Disclosure & Optimization - Sourcing Raw Materials Building Product Disclosure & Optimization - Material Ingredients; IEQc2 - Low Emitting Materials Visit mindfulmaterials.com for current transparency information Calhoun, GA (USA) - ISO 14001 Registered
Manufacturing	USA
Warranty	Limited 15-Year Residential Warranty Limited 6-Year Light Commercial Warranty