

Mixed Monolith Collection

Style	Edge	Poured	Scored
Construction	Luxury Vinyl Tile Non-ortho Phthalate	Luxury Vinyl Tile	Luxury Vinyl Tile
Classification	ASTM F1700 Class III, Type B	ASTM F1700 Class III, Type B	ASTM F2700 Class III, Type B
Total Thickness	0.197" (5 mm)	0.197" (5 mm)	0.197" (5 mm)
Wear Layer Thickness	20 mil (0.51 mm)	20 mil (0.51 mm)	20 mil (0.51 mm)
Wear Layer	Quantum Guard Elite®	Quantum Guard Elite®	Quantum Guard Elite®
Edge Treatment	Micro-bevel	Micro-bevel	Micro-Bevel
Sizes	12" x 48" (305 x 1219 mm)	6" x 48" (152 x 1219 mm) 18" x 48" (457 x 1219 mm)	6" x 48" (152 x 1219 mm)
Colors	10	6	10
Packaging	12" x 48" - 5 pcs, 19.91 ft ² (1.85 m ²), 39.11 lbs (17.74 kg)	6" x 48"- 10 pcs, 20.45 ft ² (1.9 m ²), 40.57 lbs (18.4 kg) 18" x 48"- 3 pcs, 18.08 ft ² (1.68 m ²), 35.63 lbs (16.16 kg)	6" x 48" - 10 pcs, 20.45ft ² (1.9 m ²), 40.57 lbs (18.4 kg)
Adhesive	<p>Adhesive Porous & Non-porous Substrates - Loose Lay with Perimeter Glue: Amtico Tackifier</p> <p>Porous & Non-porous Substrates - Fully adhered, releasable: Amtico Tackifier</p> <p>Porous & Non-Porous Substrates - Fully Adhered, Permanent: V-88 Fill Spread MoistureLoc Full spread, One Component</p> <p>Note: Must use XpressStep adhesive under hospital beds and heavy rolling load areas. In moreabusive conditions such as areas subject to dragging force, direct sunlight or where topical moisture would be a concern, only MoistureLoc should be used.</p>		
Installation Method	Product is non-directional. Planks can be installed monolithic, ashlar or staggered to create a random appearance. Suggested installation combinations are also available in the brochure.		
Testing	<p>HUD/FHA</p> <p>Flexibility (ASTM F137)</p> <p>Dimensional Stability (ASTM F2199)</p> <p>Squareness (ASTM F2055)</p> <p>Static Load (ASTM F970 mod.)</p> <p>Residual Indentation (ASTM F1914)</p> <p>Flooring Radiant Panel (ASTM E648)</p> <p>Smoke Density (ASTM E662)</p> <p>Slip Resistance (ASTM C1028)</p> <p>Acoustic IIC (ASTM E492)</p> <p>Acoustic STC (ASTM E90)</p> <p>Resistance to Light (ASTM F1515)</p> <p>Chemical Resistance (ASTM F925)</p> <p>Resistance to Heat (ASTM F1514)</p>		
Environmental Data	<p>Indoor Air Quality</p> <p>Product Declarations</p> <p>LEED</p> <p>mindful MATERIALS</p> <p>Manufacturing</p>		
Warranty	<p>Limited 15-Year Commercial Warranty</p> <p>Limited 15-Year Quantum Guard Elite® Wear Warranty</p>		